

To convert a `.rpm` package into a `.deb` package, simply run:

```
#alien --to-deb /path/to/file.rpm
```

And vice versa:

```
#alien --to-rpm /path/to/file.deb
```

Then follow the normal process to install the package.

Snap

A snap (applicable for both Debian and Red Hat based

distributions) is a bundle of an app and its dependencies that works without modification across many different Linux distributions. Snaps are discoverable and installable from the Snap Store, an app store with millions of downloads.

Installing a package from source

To install any package from source (applicable for all distributions) you need a compiler, *make* tools, etc. These can be installed by using the following commands.

For a Debian based system, type:

```
#apt-get install build-essential
```

Syntax	Description	Example
<code>yum search STRINGS</code>	Finds any packages matching a string.	<code>yum search mysql</code> <code>yum search apache</code>
<code>yum provides COMMAND/ LIBRARY</code>	Finds the name of the package to which the specified file or feature belongs.	<code>yum provides nping</code> <code>yum provides libstdc++.so.5</code> <code>yum provides libgcc_s.so.1</code>
<code>yum whatprovides XXXXX</code>		<code>yum whatprovides libstdc++.so.5</code>
<code>yum info PACKAGE</code>	Checks name, arch, version, release, description, etc.	<code>yum info lxc</code>
<code>yum deplist PACKAGE</code>	Checks the dependencies of the packages.	<code>yum deplist vnc-server</code> <code>yum deplist tree</code>
<code>yum check-update</code>	Checks whether updates exist for the packages that are already installed on your system.	
<code>yum list</code>	Lists all the packages that are available in all enabled repositories and all the packages that are installed on your system. You can confirm an all rpm version.	<code>yum list grep httpd</code>
<code>yum list available</code>	Lists all the packages that are available to be installed in all enabled repositories.	<code>yum --disablerepo="" --enablerepo="spp" list available</code>
<code>yum install PACKAGE</code>	Installs the package.	<code>yum -y install packagename</code>
<code>yum reinstall PACKAGE</code>		
<code>yum localinstall XXXX.rpm</code>	Installs local rpm files.	<code>yum install package.rpm</code>
<code>yum remove PACKAGE</code> <code>yum erase PACKAGE</code>	Removes a particular package.	<code>yum remove lynx</code>
<code>yum update</code>	Updates all packages.	<code>yum update</code>
<code>yum update PACKAGE</code>	Updates only a package <code>yum upgrade</code> . Upgrade is the same as the update command with the <code>--obsoletes</code> flag set.	<code>yum update bash</code>

Table 4: Syntax, description and examples of yum