

```

1  using efcore_codefirst_approach.Models;
2  using System;
3  using System.Linq;
4  namespace efcore_codefirst_approach
5  {
6      0 references | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
7      class Program
8      {
9          0 references | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
10         static void Main(string[] args)
11         {
12             Console.WriteLine("ContosoDBContext getting initialized.");
13             using ContosoDBContext context = new ContosoDBContext();
14
15             Console.WriteLine("initialized..");
16             InsertRecord(context);
17             Console.WriteLine("Inserted record with the given context.");
18
19             ViewRecord(context);
20             Console.WriteLine("Queried record with the given context.");
21
22             UpdateRecord(context);
23             Console.WriteLine("Updated record with the given context.");
24
25             DeleteRecord(context);
26             Console.WriteLine("Deleted record with the given context.");
27             Console.WriteLine("Successfully executed.");
28         }
29
30         1 reference | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
31         public static void InsertRecord(ContosoDBContext context) {...}
32
33         1 reference | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
34         public static void ViewRecord(ContosoDBContext context) {...}
35
36         1 reference | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
37         public static void DeleteRecord(ContosoDBContext context) {...}
38
39         1 reference | Maheshkumar Rajaratnaveel, 1 day ago | 1 author, 1 change
40         public static void UpdateRecord(ContosoDBContext context) {...}
41     }
42 }

```

Figure 6: VS 2019 Editor

How to work with raw SQL queries

EF Core allows us to embed and execute raw SQL queries when working with a relational database. This is quite useful where you can't express queries using LINQ, say, nested reporting queries. We can use the *FromSqlRaw* extension method to begin a LINQ query based on a raw SQL query. *FromSqlRaw* can only be used on query roots, that is, directly on the *DbSet*<>.

```
C#
```

```
#region FromSqlRaw
using (var context = new DbContext())
{
    var blogs = context.Blogs
    .FromSqlRaw("SELECT * FROM dbo.Blogs")

```

```
.ToList();
foreach (Blog o in blogs)
    Console.WriteLine("Url: " + o.Url + ",
    Blog Rating: " + o.Rating);
}
#endregion
```

FromSqlInterpolated is similar to *FromSqlRaw* but allows us to use string interpolation syntax to avoid injection. As with the previous example, the value is converted to a *DbParameter* and isn't vulnerable to SQL injection. Just like *FromSqlRaw*, *FromSqlInterpolated* can only be used on query roots.

```
C#
```

```
#region FromSql InterpolatedComposed
using (var context = new DbContext())
{

```

```

ContosoDBContext getting initialized.
initialized..
1. Record inserted:Toothbrush
Inserted record with the given context.
2. Displaying record:
Cintol Bar| 544.00

Colgate| 4.90
Diary| 4545.00
Knife| 343.00
Pen| 4.91
Pencil| 199.91
Repsodent| 4.91
Sensodyne| 4.91
Toothbrush| 9.91
Toothbrush-Electric| 9.91

Queried record with the given context.
4. Updated successfully: Toothbrush-Elect
Updated record with the given context.
3. Deleted record successfully: Toothbrush
Deleted record with the given context.
Successfully executed.

```

Figure 7: Program output

```
var Name = "https://maheshk.net";
```

```
var blogs = context.Blogs
.FromSql Interpolated($"SELECT * From
Blogs Where url = {Name}")
//.OrderBy(b => b.Rating)
.ToList();
```

```
foreach (Blog o in blogs)
    Console.WriteLine("RESULT: Url: " +
    o.Url + ", Blog Rating: " + o.Rating);
}
#endregion
```

The output is shown in Figure 8.

Passing parameters

- Yes, it's recommended to use *parameterization* for raw SQL queries. When introducing any user-provided values into a raw SQL query, care must be taken to avoid SQL injection attacks. Make sure it does not contain invalid characters. Never pass a concatenated or interpolated string ("") with non-validated user-provided values into *FromSqlRaw* or *ExecuteSqlRaw*.