



TIPS & TRICKS

Hibernate in Ubuntu 18.04

The Hibernate option is not explicitly shown in Ubuntu 18.04. There are two ways to hibernate the system:

- i) When you hold the *Alt* button and click on the *Power* option, the *Pause* option will be displayed instead of the *Power* option. Click on the *Pause* option to hibernate the system.
- ii) Alternatively, click on the *Power* option and hold it. The *Pause* option will be displayed, and can be clicked on to send the system to hibernate.

—Gunasekar D., dg.gunasekar@gmail.com

Using Ansible as a Maven ci

I have created an Ansible role that works similar to continuous integration (ci), like compiling, test and packaging of a program using the *maven* command.

1. Install Ansible.
2. Download the Ansible ci role using the following command:

```
ansible-galaxy install hemanth22.ci
```

3. After downloading the Ansible role, create a *yml* file as shown below to use this role in the playbook.

```
---
- hosts: localhost
  remote_user: vagrant
  vars:
    ci_repo: [here you give the git repository url which
    contain pom.xml]
    ci_path: [By default it will create a folder with
    name: test, if you want to change foldername enter new
    foldername here]
    ci_branch: [Here mention branch name of the git
    repository]
  roles:
    - role: hemanth22.ci
      become: true
      become_method: sudo
```

4. You can find the sample test folder in the Ansible role.

```
`-- hemanth22.ci
   |-- defaults
```

```
| `-- main.yml
|-- meta
| `-- main.yml
|-- molecule
| `-- default
|   |-- molecule.yml
|   |-- playbook.yml
|   |-- tests
|   | `-- test_default.py
|   `-- yaml-lint.yml
|-- README.md
|-- tasks
| `-- main.yml
`-- tests
    |-- ansible.cfg
    |-- inventory
    `-- test.yml
```

—Hemanth Bitra, hemanthbitra@bitroid.in

Finding out the last user who logged in

Here is a simple command to check the last logged in user.

```
$last
```

This searches back through the */var/log/wtmp* file (or the file designated by the *-f* option) and displays a list of all users logged in (and out) since that file was created.

You can filter out entries for root, reboots, and any users like *raj*.

```
$last -da | egrep -v "^(root|reboot|raj) "
```

—Nataraj Ramamoorthy, raj13aug@gmail.com

END 

Share Your Open Source Recipes!

The joy of using open source software is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.