

```

buildroot.tar.gz
./
./opt/
./opt/firebird/
./opt/firebird/misc/
./opt/firebird/misc/upgrade/
./opt/firebird/misc/upgrade/ib_udf/
./opt/firebird/misc/upgrade/ib_udf/ib_udf_upgrade.sql
./opt/firebird/misc/upgrade/ib_udf/ib_udf2_params.txt
./opt/firebird/misc/upgrade/ib_udf/ib_udf_params.txt
./opt/firebird/misc/upgrade/metadata/
./opt/firebird/misc/upgrade/metadata/metadata_charset.txt
./opt/firebird/misc/upgrade/metadata/metadata_charset_drop.sql
./opt/firebird/misc/upgrade/metadata/metadata_charset_create.sql
./opt/firebird/misc/upgrade/security/
./opt/firebird/misc/upgrade/security/security_database.sql
./opt/firebird/misc/upgrade/security/security_database.txt
./opt/firebird/misc/intl.sql
./opt/firebird/misc/firebird.xinetd
./opt/firebird/UDF/
./opt/firebird/UDF/ib_udf.sql
./opt/firebird/UDF/ib_udf.so
./opt/firebird/UDF/fbudf.sql
./opt/firebird/UDF/ib_udf2.sql
./opt/firebird/UDF/fbudf.so
./opt/firebird/WhatsNew
./opt/firebird/aliases.conf
..... TOO MUCH OUTPUT .....
root@host:/root/FirebirdCS-3.0.4.33054-0.i686# mkdir /opt/
firebird01
root@host:/root/FirebirdCS-3.0.4.33054-0.i686# cp -R opt/
firebird/* /opt/firebird01/

```

Now that your Firebird directory has been created, we can check if the dependencies for *libfbclient* are met. Run *ldd* in *libfbclient.so.3.0.4* inside the */opt/firebird01/lib* you just created. As long as you don't come across anything such as *not found*, you are good.

```

root@host:/opt/firebird01/lib# ldd libfbclient.so.3.0.4
linux-gate.so.1 => (0x00635000)
libm.so.6 => /lib/libm.so.6 (0x00110000)
libdl.so.2 => /lib/libdl.so.2 (0x006f9000)
libncurses.so.5 => /lib/libncurses.so.5 (0x00a46000)
libpthread.so.0 => /lib/libpthread.so.0 (0x00281000)
libc.so.6 => /lib/libc.so.6 (0x0029b000)
/lib/ld-linux.so.2 (0x00f59000)

```

Now, we need to add a new user called *firebird*, which we will use to run the Firebird server:

```

root@host:/# groupadd firebird
root@host:/# useradd -d /opt/firebird01 -s /bin/false -c
"Firebird Database Owner" -g firebird firebird

```

Step 2: Setting up the first environment

Firebird needs to have a default password set for the *SYSDBA* user, which is the admin user of the Firebird server. To set this up, use the following code:

```

root@host:/opt/firebird01/lib# export FIREBIRD=/opt/firebird01/
root@host:/opt/firebird01/lib# export LD_LIBRARY_PATH=$LD_
LIBRARY_PATH:/opt/firebird01/lib/
root@host:/opt/firebird01/lib# cd ../bin
root@xubuntu:/opt/firebird01/bin# ./gsec
GSEC> modify SYSDBA -pw masterkey
Warning - maximum 8 significant bytes of password used
GSEC> quit

```

Let's make a copy of the working environment:

```

root@host:/opt# cd /opt
root@host:/opt# cp firebird01/ firebird02/ -R

```

Now, let's change the names of the executables in both directories:

```

root@host:/opt# mv firebird01/bin/fb_inet_server firebird01/bin/
fb_inet_server01
root@host:/opt# mv firebird02/bin/fb_inet_server firebird02/bin/
fb_inet_server02

```

So, moving forward, let's set up *xinetd* to start the right server, depending on which port the server receives incoming connections from.

Step 3: Xinetd

Now we have two separate installations of the Firebird 3.0.4 Classic Server. The next step will be to set up *xinetd* to associate different ports with different Firebird servers.

Xinetd is a connection manager, a so-called Super Internet Server, which will launch a specified server only when a user is trying to connect to a specified port. For instance, if you have an ftp server set up that is listening on Port 21, when a connection is being made to Port 21, *xinetd* will launch the service associated with this port. Let's look into the following example for more clarity.

Let's first create the Firebird service entry. Therefore, open up */etc/services*. Remove the following two lines:

```

gds_db      3050/tcp      # InterBase server
gds_db      3050/udp

```

Add the above two lines to the end of the following file.

```

# Local services
firebird01  3050/tcp      # Firebird01
firebird01  3050/udp
firebird02  3060/tcp      # Firebird02
firebird02  3060/udp

```