

month's name, you can use the *ts-month-abbr* function as shown below:

```
(ts-month-abbr (ts-now))
"Jul"
```

The *ts-month-name* function can be used to obtain the full name of the month. For example:

```
(ts-month-name (ts-now))
"July"
```

The day of the week starts from Monday and has an index 1, while Sunday has an index 7. If you need the numeric value for the day of the week, use the *ts-day* function as indicated below:

```
(ts-day (ts-now))
5
```

The *ts-year* API returns the year. In our example, it is '2019' as shown below:

```
(ts-year (ts-now))
2019
```

The hour, minute and seconds can be retrieved using the *ts-hour*, *ts-minute* and *ts-second* functions, respectively. Examples of these functions are given below:

```
(ts-hour (ts-now))
18

(ts-minute (ts-now))
19

(ts-second (ts-now))
5
```

The UNIX timestamps are in UTC, by default. The *ts-tz-offset* function returns the offset from UTC. The Indian Standard Time (IST) is five-and-a-half-hours ahead of UTC and hence this function returns '+0530' as shown below:

```
(ts-tz-offset (ts-now))
"+0530"
```

The *ts-tz-abbr* API returns an abbreviated form of the time zone. In our case, 'IST' is returned for the Indian Standard Time.

```
(ts-tz-abbr (ts-now))
"IST"
```

The *ts-adjustf* function applies the time adjustments passed to the timestamp and the *ts-format* function formats the timestamp as a string. A couple of examples are given below:

```
(let ((ts (ts-now)))
  (ts-adjustf ts 'day 1)
  (ts-format nil ts))
"2019-07-06 18:23:24 +0530"
```

```
(let ((ts (ts-now)))
  (ts-adjustf ts 'year 1 'month 3 'day 5)
  (ts-format nil ts))
"2020-10-10 18:24:07 +0530"
```

You can use the *ts-dec* function to decrement the timestamp. For example:

```
(ts-day-name (ts-dec 'day 1 (ts-now)))
"Thursday"
```

The threading macro syntax can also be used with the *ts-dec* function as shown below:

```
(->> (ts-now) (ts-dec 'day 2) ts-day-name)
"Wednesday"
```

The UNIX epoch is the number of seconds that have elapsed since January 1, 1970 (midnight UTC/GMT). The *ts-unix* function returns an epoch UNIX timestamp as illustrated below:

```
(ts-unix (ts-adjust 'day -2 (ts-now)))
1562158551.0 ;; Wednesday, July 3, 2019 6:25:51 PM GMT+05:30
```

An hour has 3600 seconds and a day has 86400 seconds. You can compare epoch timestamps as shown in the following example:

```
(/ (- (ts-unix (ts-now))
      (ts-unix (ts-adjust 'day -4 (ts-now))))
  86400)
4
```

The *ts-difference* function returns the difference between two timestamps, while the *ts-human-duration* function returns the property list (*plist*) values of years, days, hours, minutes and seconds. For example:

```
(ts-human-duration
  (ts-difference (ts-now)
                  (ts-dec 'day 3 (ts-now))))
(:years 0 :days 3 :hours 0 :minutes 0 :seconds 0)
```