

```
chdir: "{{ guile_home }}"
```

The above playbook can be invoked using the following command:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/guile.yml --tags test -vv -K
```

Documentation

TeX is required to generate PDFs from the built-in documentation sources in the GNU Guile code repository. The following Ansible playbook will generate the PDF documentation:

```
- name: Generate documentation
  hosts: guile
  become: yes
  become_method: sudo
  gather_facts: yes
  tags: [docs]

vars:
  guile_home: "/home/parabola/guile"

tasks:
  - name: Install texlive-core
    package:
      name: texlive-core
      state: latest

  - name: Generate documentation
    command: make pdf
    args:
      chdir: "{{ guile_home }}"
```

A sample execution output of invoking the above playbook is given below:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/guile.yml --tags docs -K
SUDO password:

PLAY [Repository setup] *****
TASK [Gathering Facts] *****
ok: [guile]
PLAY [Build guile] *****
TASK [Gathering Facts] *****
ok: [guile]
PLAY [Install guile] *****
TASK [Gathering Facts] *****
ok: [guile]
PLAY [Test guile] *****
TASK [Gathering Facts] *****
ok: [guile]
PLAY [Generate documentation] *****
```

```
TASK [Gathering Facts] *****
ok: [guile]
TASK [Install texlive-core] *****
changed: [guile]
TASK [Generate documentation] *****
changed: [guile]
PLAY [Run benchmarks] *****
TASK [Gathering Facts] *****
ok: [guile]
PLAY RECAP *****
guile : ok=8 changed=2
unreachable=0 failed=0
```

The following PDFs are built and available in the GNU Guile sources directory:

```
$ find . -name *.pdf
./doc/ref/scheme.pdf
./doc/ref/gds.pdf
./doc/ref/guile.pdf
./doc/ref/hierarchy.pdf
./doc/r5rs/r5rs.pdf
```

Benchmarking

A *benchmark-guile* script is available to run benchmarks against the built binaries. The following Ansible playbook can be used to run benchmarking:

```
- name: Run benchmarks
  hosts: guile
  gather_facts: yes
  tags: [benchmarks]

vars:
  guile_home: "/home/parabola/guile"

tasks:
  - name: Run benchmarks
    command: ./benchmark-guile
    args:
      chdir: "{{ guile_home }}"
```

The above playbook can be invoked using the following command:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/guile.yml --tags benchmarks -vv -K
```

You can learn more about GNU Guile from its home page at <https://www.gnu.org/software/guile/>. 

By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.