

```
{
    var age int // variable declaration
    fmt.Println("my age is", age)
}
```

Since the variable, *age*, is not assigned any value, Go automatically initialises it with the zero value of the variable's type. We can declare multiple variables at once, as follows:

```
var salary, amount int
```

Go enables us to declare multiple or single variables and initialise them at the same time:

```
var age, salary = 25, 30000
```

```
package main
import "fmt"
func main()
{
    var number, amount = 10, 15
    var sum = 20
    fmt.Println(number, amount, sum) prints the o/p, 10 15 20
}
```

Go has awesome shorthand for declaring and initialising a variable. The syntax is:

```
variable := value

number := 10
amount := 15
fmt.Println(number, amount)
```

Printf can also be used along with the corresponding control strings in Go:

```
package main
import "fmt"
func main() {
    var i int
    var f float64
    var b bool
    var s string
    var name = "Ann"
    fmt.Printf("%T %T %T %T\n", i, f, b, s) // Prints type of the variable
    fmt.Printf("%v %v %v %q \n", i, f, b, s) //prints initial value of the variable
    fmt.Printf("type : %T & value : %v\n", name, name)
}
```

The output will be:

```
int float64 bool string
0 0 false " "
```

```
type: string & value : Ann
```

Decision making statements

1. *If* statement: An *if* statement consists of a Boolean expression followed by one or more statements:

```
package main
import "fmt"
func main()
{
    number := 10
    if number >= 5
    {
        fmt.Println("I will print the value:", number)
    }
}
```

Unlike in other languages like C, the curly braces are mandatory even if there is only one statement between the { }.

2. *If..else* statement

```
package main
import "fmt"
func main()
{
    num := 10
    if (num > 0)
    { //checks if number is positive
        fmt.Println("the number is positive")
    }
    else
    {
        fmt.Println("the number is negative")
    }
}
```

Nested if..else : (Complete using greatest of 3)

```
package main
import "fmt"
func main()
{
    x:= 10 y:=20
    if( x >=10 ) {
        if( y >= 10 )
        {
            fmt.Printf("Inside nested If Statement \n")
        }
    }
    fmt.Printf("Value of x is : %d\n", x );
    fmt.Printf("Value of y is : %d\n", y );
}
```

Switch in Go

Switch statements are used to check conditionals with