

```

defaults
    mode                http
    log                 global
    option              httplog
    option              dontlognull
    option http-server-close
    option forwardfor   except 127.0.0.0/8
    option              redispatch
    retries             3
    timeout http-request 10s
    timeout queue       1m
    timeout connect     10s
    timeout client      1m
    timeout server      1m
    timeout http-keep-alive 10s
    timeout check       10s
    maxconn             3000

listen haproxy-monitoring *:8080
    mode http
    option forwardfor
    option httpclose
    stats enable
    stats show-legends
    stats refresh 5s
    stats uri /stats
    stats realm Haproxy\ Statistics
    stats auth admin:password
    stats admin if TRUE
    default_backend app-main

frontend main
    bind *:80
    option http-server-close
    option forwardfor
    default_backend app-main

backend app-main
    balance roundrobin
    option httpchk HEAD / HTTP/1.1\r\nHost:\ localhost
{% for item in groups['web'] %}
    server {{ hostvars[item]['inventory_hostname'] }} {{
hostvars[item]['ansible_default_ipv4']['address'] }}:80 check
{% endfor %}

```

The rsyslog software will be used to collect the HAProxy logs. The */etc/rsyslog.conf* configuration is updated to load the UDP Syslog Input Module (imudp) and to run a UDP server on Port 514. A */etc/rsyslog.d/haproxy.conf* configuration file is created, the contents of which are as follows:

```

local2.=info    /var/log/haproxy-access.log
local2.notice   /var/log/haproxy-info.log

```

The firewall is updated to allow Port 8080, and the rsyslog server is restarted. The final step is to start the HAProxy server and wait for it to listen on Port 8080. The complete Ansible playbook to install and configure HAProxy is given below:

```

- name: Setup HAProxy
  hosts: front
  become: yes
  become_method: sudo
  gather_facts: yes
  tags: [haproxy]

tasks:
  - name: Yum update
    yum: name=* update_cache=yes state=present

  - name: Install HAProxy
    package:
      name: haproxy
      state: present

  - name: Add Nginx servers to /etc/hosts
    lineinfile:
      path: /etc/hosts
      line: "{{ hostvars[item]['ansible_default_ipv4']
['address'] }}" "{{ hostvars[item]['inventory_hostname'] }}"
      state: present
      with_items: "{{ groups['web'] }}"

  - name: Backup default haproxy.cfg
    command: mv haproxy.cfg haproxy.cfg.orig
    args:
      chdir: /etc/haproxy

  - name: Create new haproxy.cfg
    template:
      src: ../../files/haproxy.cfg.j2
      dest: /etc/haproxy/haproxy.cfg
      mode: 0644

  - name: Update /etc/rsyslog.conf
    lineinfile:
      path: /etc/rsyslog.conf
      regexp: "{{ item.regexp }}"
      line: "{{ item.line }}"
      with_items:
        - { regexp: '#$ModLoad imudp', line: '$ModLoad
imudp' }
        - { regexp: '#$UDPServerRun 514', line:
'$UDPServerRun 514' }

  - name: Create /etc/rsyslog.d/haproxy.conf
    copy:

```