



Switching between running the process in the background and the foreground

While working with any Linux command, you can press 'Ctrl Z' to run the process in the background. This will work for all the Linux commands and processes. The 'ps aux' command will show the 'Ctrl Z' process as 'T' or terminated. To run the process in the foreground again, just type the following command:

```
$fg
```

The background process will again become active in the foreground. For example, to work with the Python terminal, type the following code:

```
test@laptop-hp:~$ python
Python 2.7.12 (default, Nov 12 2018, 14:36:49)
[GCC 5.4.0 20160609] on linux2
Type "help", "copyright", "credits" or "license" for more
information.
>>>
```

The Python terminal of '>>>' will be activated. Without terminating the Python terminal, just press 'Ctrl Z', which will give the following output:

```
[1]+  Stopped                  python
```

To activate this process again, type the following command and click on *Enter*:

```
$fg
```

The Python terminal will become active again.

—Tushar Kute, tushar@tusharkute.com

Run .bat files without leaving Git bash in Windows

Git bash is a replacement for CMD in Windows. It helps you run Linux commands too, but Git bash cannot run Windows batch (.bat) files. With this tip, you need not leave Git bash to run .bat files.

Let us create a batch file under the folder *batchfiles*. Open Notepad and type the following command:

```
@echo Hello world from bat file.
```

Save this file as *helloWorld.bat* under the *batchfiles* folder. Change the directory to the folder containing .bat files in Git bash, as follows:

```
cd batchfiles
```

Now try to run .bat files from Git bash by typing the following command, which will throw up the error message 'command not found'.

```
helloWorld.bat
```

All you need to do to run a .bat file is to execute the command ``cmd`` and you will see a Windows command prompt opening. Next, type the name of your batch file ``helloWorld.bat`` and you can see the .bat file getting executed. To leave CMD and get back to Git bash, type ``exit``.

—Dhananjaya Balaji, pessebalu@gmail.com

How to change the MAC address in a Linux based OS

Given below are the steps that need to be followed to change the existing MAC address of your Ethernet card.