

```
'line': 'wal_level = hot_standby'})
changed: [host1] => (item={'regex': '#synchronous_commit =
on', 'line': 'synchronous_commit = local'})
changed: [host1] => (item={'regex': '#archive_mode = off',
'line': 'archive_mode = on'})
changed: [host1] => (item={'regex': "#archive_command =
'", 'line': "archive_command = 'cp %p /var/lib/pgsql/9.6/
archive/%f'"})
changed: [host1] => (item={'regex': '#max_wal_senders = 0',
'line': 'max_wal_senders = 2'})
changed: [host1] => (item={'regex': '#wal_keep_segments =
0', 'line': 'wal_keep_segments = 2'})
changed: [host1] => (item={'regex': "#synchronous_
standby_names = '", 'line': "synchronous_standby_names =
'slave01'"})

TASK [Create archive directory] *****
changed: [host1]

TASK [Update pg_hba.conf] *****
changed: [host1]

TASK [Restart PostgreSQL server] *****
changed: [host1]

TASK [Create replication user] *****

[WARNING]: Consider using 'become', 'become_method'
'become_user' rather than running sudo

changed: [host1]

PLAY [Setup pgslave] *****

TASK [Gathering Facts] *****
ok: [host2]

PLAY RECAP *****

host1                : ok=7    changed=5
unreachable=0        failed=0
host2                : ok=2    changed=0
unreachable=0        failed=0
```

The PostgreSQL slave

The last step is to configure the PostgreSQL slave instance to receive data from the master instance. The PostgreSQL server is initially stopped, the `var/lib/pgsql/9.6/data` directory is backed up, and a new `data/` directory is created. The initial data is fetched from the master using `pg_basebackup`. The replica user password can be encrypted and stored using Ansible Vault. The `postgresql.conf` file is updated, a `recovery.conf` file

is created, and the PostgreSQL server on the slave instance is started. The Ansible playbook to configure the replication slave is given below:

```
- name: Setup pgslave
  hosts: pgslave
  become: yes
  become_method: sudo
  gather_facts: yes
  tags: [pgslave]

vars:
  replica_password: 'replica123'

tasks:
  - name: Stop PostgreSQL server
    systemd:
      name: postgresql-9.6
      state: stopped

  - name: Move data backup
    shell: mv data data-backup
    args:
      chdir: /var/lib/pgsql/9.6/

  - name: Create data directory
    file:
      path: /var/lib/pgsql/9.6/data
      mode: 0700
      owner: postgres
      group: postgres
      state: directory

  - name: Backup initial data from master
    shell: su - postgres -c "PGPASSWORD={{ replica_password
}} pg_basebackup -w -h {{ hostvars['host1'].ansible_default_
ipv4.address }} -U replica -D /var/lib/pgsql/9.6/data -P
--xlog"

  - name: Update /var/lib/pgsql/9.6/data/postgresql.conf
    lineinfile:
      path: /var/lib/pgsql/9.6/data/postgresql.conf
      regexp: "{{ item.regex }}"
      line: "{{ item.line }}"
    with_items:
      - { regex: "#listen_addresses = 'localhost'", line:
"listen_addresses = '{{ ansible_default_ipv4.address }}' " }
      - { regex: "#hot_standby = off", line: "hot_standby
= on" }

  - name: Create recovery.conf
    blockinfile:
```