

can use the *f-swap-ext* function as follows:

```
(f-swap-ext "/etc/resolv.conf" "conf.bak")
"/etc/resolv.conf.bak"
```

The actual source code implementation in *f.el* is given below:

```
(defun f-swap-ext (path ext)
  "Return PATH but with EXT as the new extension.
EXT must not be nil or empty."
  (if (s-blank? ext)
      (error "Extension cannot be empty or nil")
      (concat (f-no-ext path) "." ext)))
```

The extension is checked to see if it is empty. If it is not blank, then the path without the present extension is concatenated with the new extension and returned.

The *f-base* API provides you just the file name without the extension.

```
(f-base "/etc/resolv.conf")
"resolv"
```

A file name path that contains the tilde (~) symbol will be expanded to return the long version using the *f-long* construct as shown below:

```
(f-long "~/downloads")
"/home/guest/downloads"
```

If you need a trailing "/" at the end of a file name path, you can apply the *f-slash* function. For example:

```
(f-slash "/home/guest/docs")
"/home/guest/docs/"
```

The *f-full* API will return the absolute PATH as well as the trailing slash, as indicated below:

```
(f-full "~/code")
"/home/guest/code/"
```

I/O

The *f.el* library also provides functions to perform read/write operations on files. You can read the file contents in UTF-8 format using the *f-read-text* API:

```
(f-read-text "/etc/resolv.conf" 'utf-8)

# Generated by NetworkManager
nameserver 192.168.0.1
```

You can write text to a file using the *f-write-text* function,

as shown below:

```
(f-write-text "Hello World!" 'utf-8 "/tmp/hello.txt")
nil
$ cat /tmp/hello.txt
Hello World! $
```

Appending text to a file can be accomplished using the *f-append-text* function, as illustrated below:

```
(f-append-text "\n" 'utf-8 "/tmp/hello.txt")
nil
$ cat /tmp/hello.txt
Hello World!
$
```

Destructive

A directory can be created using the *f-mkdir* API. On success, it returns the value *nil*. An example is shown below:

```
(f-mkdir "/tmp" "test")
nil
```

You can delete a directory with the *f-delete* function and *nil* is returned on success.

```
(f-delete "/tmp/test")
nil
```

A symbolic link file can be created using *f-symlink* with the argument *target linkpath*, where the linkpath is created for the target. *Nil* is returned on success.

```
(f-symlink "/etc/resolv.conf" "/tmp/resolv.conf")
nil
```

You can rename a file using the *f-move* API as shown below:

```
(f-move "/tmp/hello.txt" "/tmp/hello-world.txt")
nil
```

The *f-copy* function can be used to copy a file or directory from a source to a target location. For example:

```
(f-copy "/tmp/hello-world.txt" "/tmp/greetings.txt")
nil
```

You can copy an entire directory's contents from a source to a target using the *f-copy-contents* construct as illustrated below:

```
(f-mkdir "/tmp" "nginx")
nil
```