

```
(f-copy-contents "/etc/nginx" "/tmp/nginx")
nil
```

A file's last modification date can be updated using the *f-touch* API as follows:

```
$ ls -l /tmp/hello-world.txt
-rw-r--r-- 1 guest guest 14 Feb 7 16:49 hello-world.txt
(f-touch "/tmp/hello-world.txt")
t
$ ls -l /tmp/hello-world.txt
-rw-r--r-- 1 guest guest 14 Feb 7 17:00 hello-world.txt
```

Predicates

The *f.el* library provides a number of predicate functions that you can use to make assertions on files and directories. The *f-exists?* function returns *true* if the PATH exists. For example:

```
(f-exists? "/tmp/hello-world.txt")
t
```

The actual function definition in the source code is as follows:

```
(defun f-exists? (path)
  "Return t if PATH exists, false otherwise."
  (file-exists-p path))
```

It uses the GNU Emacs *built-in* *file-exists-p* function to return *true* if the PATH exists, or returns *false* otherwise.

You can check if a file or directory exists using the *f-file?* and *f-directory?* APIs, respectively.

```
(f-file? "/tmp/hello-world.txt")
t
```

```
(f-file? "/tmp/test")
nil
```

```
(f-directory? "/tmp/test")
t
```

```
(f-directory? "/tmp/hello-world.txt")
nil
```

The *f-symlink?* function returns true if the given PATH is a symbolic link file.

```
(f-symlink? "/tmp/resolv.conf")
t
```

You can check if a file has read, write or executable permissions using the *f-readable?*, *f-writable?* and *f-executable?* functions, respectively, as illustrated below:

```
(f-readable? "/etc/resolv.conf")
t
```

```
(f-writable? "/etc/resolv.conf")
nil
(f-executable? "/etc/resolv.conf")
nil
```

```
(f-executable? "/usr/bin/date")
t
```

Others

You can obtain the size of a file using the *f-size* API as shown below:

```
(f-size "/tmp/resolv.conf")
16
```

The *f-depth* API provides the depth of the PATH as illustrated in the following examples:

```
(f-depth "/")
0
(f-depth "/etc")
1
(f-depth "/etc/nginx")
2
```

The list of files and directories in a PATH can be obtained using the *f-entries* function.

```
(f-entries "/etc") =>
("/etc/.pwd.lock" "/etc/.updated" "/etc/GNUstep"
 "/etc/ImageMagick-6" "/etc/ImageMagick-7"
 "/etc/NetworkManager" "/etc/UPower" "/etc/X11"
 "/etc/adjtime" "/etc/ansible" "/etc/arch-release"
 "/etc/avahi" ...)
```

The 'f-directories' API provides the list of directories in a PATH as shown below:

```
(f-directories "/tmp")
("/tmp/.ICE-unix" "/tmp/.Test-unix" "/tmp/.X11-unix"
 "/tmp/.XIM-unix" "/tmp/.font-unix" "/tmp/babel-awGAhc"
 "/tmp/emacs1000" "/tmp/nginx" "/tmp/test")
```

You are encouraged to refer to the README file at <https://github.com/rejeep/f.el/blob/master/README.md> for more examples and usage. 

 By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.