



Umask default setting

Umask sets the calling process's file mode creation mask to *mask* and 0777 (i.e., only the file permission bits of *mask* are used), and returns the previous value of the *mask*. *Umask* is used by *open*, *mkdir* and other system calls that create files to modify the permissions placed on newly created files or directories. Specifically, permissions in *umask* are turned off from the mode argument to *open* and *mkdir*.

Alternatively, if the parent directory has a default ACL, *umask* is ignored, the default ACL is inherited, the permission bits are set based on the inherited ACL, and permission bits absent in the mode argument are turned off.

Given below is a command to check the default setting of *umask*:

```
root@client:~# umask -S
u=rwx,g=rx,o=rx
root@client:~#
```

—Rupin Puthukudi,
rupinmp@gmail.com

Reset the temporary network setting

Very often we need to do temporary network settings and do not need them later. When you no longer need a temporary configuration, you can easily reset it with the following command:

```
$ ip addr flush <interface name>
```

Alternatively, you can reboot your server to reset the temporary configuration.

—Rupin Puthukudi,
rupinmp@gmail.com

Find almost similar and duplicate directories

The following script will find sets of directories (under the current directory) that are *almost* as well as *exact* duplicates of each other.

So if one or two files have a few small changes in them, the script will still list the directories that match. That takes a bit of work to achieve. You can create the script in any text editor and then execute it.

Open a Vim editor, as follows:

```
#vi myscript_dfolder
```

Now type the following content in the file:

```
#!/bin/bash/

for d in `find $PWD -type d -print`;
do
    echo `cd $d;ls -lARs .|cksum|sed 's/ /_/'` $d;
done | awk '{c[$1]++; s[$1]=s[$1] " " $2}
END
{
for (i in c)
{if (c[i]>1) print s[i]}
}
```

—Aditya Dhanraj, adityadhanraj1312@gmail.com