

```

register: encrypted

- assert:
  that:
    - "encrypted.rc == 0"

- name: Check /tmp
  shell: mount | grep /tmp | grep -E 'nosuid.*nodev'
  register: tmp

- assert:
  that:
    - "tmp.rc == 0"

- name: Check /dev/shm
  shell: mount | grep /dev/shm | grep -E
'nosuid.*nodev.*noexec'
  register: tmp

- assert:
  that:
    - "tmp.rc == 0"

- name: Change file mode for /boot, /etc/iptables
  file:
    path: "{{ item }}"
    mode: 0700
  with_items:
    - /boot
    - /etc/iptables

- name: Update /etc/pam.d/system-login
  lineinfile:
    path: /etc/pam.d/system-login
    regexp: '^auth.*required.*pam_tally.so'
    line: 'auth      required  pam_tally.so
deny=2 unlock_time=600 onerr=succeed file=/var/log/faillog'

- name: Update /etc/security/limits.conf
  lineinfile:
    path: /etc/security/limits.conf
    insertbefore: '# End of file'
    line: "{{ item }}"
  with_items:
    - '* soft nproc 100'
    - '* hard nproc 200'

- name: Update /etc/pam.d/su
  lineinfile:
    path: /etc/pam.d/su
    regexp: '^#auth      required  pam_wheel.so use_
uid'

```

```

line: 'auth      required  pam_wheel.so use_uid'

- name: Update /etc/pam.d/su-1
  lineinfile:
    path: /etc/pam.d/su-1
    regexp: '^#auth      required  pam_wheel.so use_uid'
    line: 'auth      required  pam_wheel.so use_uid'

- name: Restrict access to kernel logs
  copy:
    src: ../../files/50-dmesg-restrict.conf
    dest: /etc/sysctl.d/50-dmesg-restrict.conf
    owner: root
    group: root
    mode: 0644

- name: Restrict access to kernel pointers in procs
  copy:

    src: ../../files/50-kptr-restrict.conf
    dest: /etc/sysctl.d/50-kptr-restrict.conf
    owner: root
    group: root
    mode: 0644

- name: Disable root login
  lineinfile:
    path: /etc/ssh/sshd_config
    regexp: '^#PermitRootLogin'
    line: 'PermitRootLogin no'

- name: Disable root console logins
  replace:
    path: /etc/securetty
    regexp: '^(?!#)(.*)'
    replace: '# \1'

```

You can invoke the above playbook using:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/parabola.yml -vv -K
```

The `-vv` represents the verbosity in the Ansible output. You can use up to four `v`'s for a more detailed output. The `-K` option prompts for the `sudo password` for the guest Parabola user account.

You are encouraged to read the security guide and best practices for Parabola GNU/Linux-libre available at <https://wiki.parabola.nu/Security> for more information. **END** 

By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.