

Minio can persist the objects. While there are multiple disks and other options that you can provide while starting it, we will go with the basic use case, i.e., use one folder (directory) to store our persistent data. This can be any accessible drive on your machine. In my case, I chose to go with the `d:\minio-data` folder.

Starting the Minio server is as simple as using the server sub-command for the Minio executable and providing the PATH, as shown below:

```
D:\minio>minio server d:\minio-data
```

```
Endpoint: http://169.254.224.241:9000
http://10.21.11.176:9000 http://169.254.68.108:9000
http://169.254.83.68:9000 http://192.168.99.1:9000
http://127.0.0.1:9000
AccessKey: MDMU09WUX03ZEFDKSA5B
SecretKey: 6V/xJLyW1XtL78kq9Jl3kuGogNzPj82atit/wBaR
Region: us-east-1
S3 ARNs: <none>
```

```
Browser Access:
http://169.254.224.241:9000 http://10.21.11.176:9000
http://169.254.68.108:9000 http://169.254.83.68:9000
http://192.168.99.1:9000 http://127.0.0.1:9000
```

```
Command-line Access: https://docs.minio.io/docs/minio-client-quickstart-guide
$ mc.exe config host add myminio
http://169.254.224.241:9000 MDMU09WUX03ZEFDKSA5B 6V/
xJLyW1XtL78kq9Jl3kuGogNzPj82atit/wBaR
```

```
Object API (Amazon S3 compatible):
Go: https://docs.minio.io/docs/golang-client-quickstart-guide
Java: https://docs.minio.io/docs/java-client-quickstart-guide
```




Figure 1: Minio access page




Figure 2: Create bucket option

Figure 3: List of buckets

```
Python: https://docs.minio.io/docs/python-client-quickstart-guide
JavaScript: https://docs.minio.io/docs/javascript-client-quickstart-guide
```

```
Drive Capacity: 64 GiB Free, 304 GiB Total
```

On successfully starting up, you should note the server access key and the secret key that are provided. You will need these to access the Web user interface that Minio also provides. Additionally, if you are looking to use the Minio API to integrate into your applications, you will need these key values; so, keep them handy and secure.

Accessing the Minio server

In the startup log shown in the console, you will notice multiple URLs. Since we are using the same machine, we can go with localhost for accessing the Minio server. Simply launch a browser and visit the `http://localhost:9000` address. This will bring up the page as shown in Figure 1.

Provide the access key and the secret key, after which you are good to go. Minio organises the objects into a collection of buckets. A bucket can be conceptually thought of as a folder that holds a collection of objects.

Click on the + sign at the right bottom to get an option to either create a bucket or upload a file (Figure 2).

Select the *Create bucket* option and give it a name, e.g., *backups*. This will create a bucket in the list of buckets shown in the left pane.

You can now use the interface itself to add files to the specific bucket. This structure is required because Minio is also compatible with cloud storage services like Amazon S3; so, it becomes easier for it to synchronise with the same.

Think for a while about how the process of setting up and running Minio is a straightforward exercise. Imagine if you set this up on your local network for your personal use or even for your team/enterprise. You can immediately start accessing the server and working with buckets and files.

You will definitely need to provide the Object Store in your applications. For example, it could be an extension to your existing application, using which people can upload files that Minio will store and manage. Other use cases