

(let my new user's name be 'newusername'):

```
$sudo adduser newusername
```

It will ask you to enter the user's password twice, so do that step. Just press *Enter* on being asked the user's information. When prompted for the question, "Is the information correct [Y/N]", type *Y* and hit *Enter*. Now enter the following command:

```
$sudo visudo
```

You will find the following text in the file:

```
# User privilege specification
root ALL=(ALL:ALL) ALL
```

Then add the following code ahead of it:

```
newusername ALL=(ALL:ALL) ALL
```

Press *Ctrl-X*, *Y* and then press *Enter*.

You now have a new user with root access named 'newusername'.

—Yash Jain, yashjain.lnm@gmail.com



Making boot process reports visible in Ubuntu

By default, the boot process reports of your operating system are hidden behind a nice boot splash screen. For troubleshooting and testing purposes, it can be very useful to make them visible.

You can do that as follows:

1. In the Grub boot menu, select the boot line of Ubuntu.
2. Press the 'E' key.
3. Remove the words 'quiet splash' from the boot line.
4. Press the *Ctrl+X* keys.

Now your system will boot once, and then your boot process reports will be visible.

—Shouvik Mitra, shouvikmitra@outlook.com



Get your public IP address and host name

With the help of the following commands you can get the external IP address of the server:

```
$curl ifconfig.me
```

```
...or:
```

```
$curl ifconfig.co
```

Here is how you can get the hostname and fully qualified

domain name of the Linux host. Use the following commands:

```
# hostname
# hostname -f
```

The first command should show the short hostname and the second should show the fully qualified domain name (FQDN) of the Linux host.

—Munish Kumar, munishtotech@gmail.com



Copy all files excluding certain file types

We often have to copy all files excluding certain file type(s). There are many ways to solve this problem, but let's look at the easiest and most efficient solution. For this purpose, we are going to use the 'extglob' flag of the bash shell, which enables the extended pattern matching feature for pathnames. Let us illustrate this with an example.

We have a directory which contains various files:

```
[bash]$ ls
a.cpp a.html a.java a.mp3 a.txt b.cpp b.html b.java
b.mp3 b.txt
```

Now we want to copy all files except the .txt and .mp3 files. So first enable extended pattern matching as follows:

```
[bash]$ shopt -s extglob # enables extended pattern matching
```

Let us execute the following command to exclude .txt and .mp3 files:

```
[bash]$ cp !(*.mp3*.txt) /tmp/src/
```

Let us verify that the required files are copied to the new location:

```
bash$ ls /tmp/src/
a.cpp a.html a.java b.cpp b.html b.java
```

Yes! It worked and we got the expected result.

—Narendra Kangralkar,
narendrakangralkar@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.