



Recording the commands in a script session

Here is a simple tip that will help you to record the terminal keystrokes session and its output in a file.

```
$ script file1.txt
```

Give the script command shown above, and the details will be recorded in the file *file1.txt*.

```
$ ls
$ ps -el
$ lsblk
$ exit
```

The last command stops the recording for the executed commands.

```
$ cat file1.txt
```

The command given above will show all the commands that were executed on the terminal during the script session.

—Pritam Nipane, pritamnipane@gmail.com



File attributes—making files immutable and undeletable

File attributes allow customisation of certain file-related operations. By changing the attributes, we can alter the nature of the file. Some of the file attributes are listed below:

- a: append only
- i: immutable
- s: secure deletion
- t: no tail-merging
- u: undeletable
- D: synchronous directory updates
- S: synchronous updates

(For detailed information, please read the man page of *chattr*). *lsattr* is the command used to list file attributes.

For example:

```
$ lsattr test.txt
```

```
-----e---- test.txt
```

chattr is used to change the attribute.

To make the *test.txt* file unmodifiable, use the command shown below:

```
# chattr +i test.txt
```

Now the file has become immutable. This is very handy when you are in a multi-user environment.

—Noble Philip, noblephilip@outlook.com



Upload and share any file from the Linux command line with *transfer.sh*

Sysadmins and most of us face a problem while uploading and sharing files, which is why *transfer.sh* excites me a lot. Here is a tip on how to use this service.

You can use *Curl* to upload a file as shown below:

```
curl --upload-file filename.txt https://transfer.sh/filename.txt
```

This will generate a download link (<https://transfer.sh/bjc3g/filename.txt>).

Now, we can use the generated link to download a file using *wget*:

```
wget https://transfer.sh/bjc3g/filename.txt
```

You can upload a file using Bash, too, with the *transfer* command. For that, you need to add the following lines to *.bashrc*:

```
transfer()
{ if [ $# -eq 0 ];
  then echo -e "No arguments specified. Usage:\neco transfer /tmp/
test.md\ncat /tmp/test.md | transfer test.md";
  return 1;
fi
tmpfile=$(mktemp -t transferXXX);
if tty -s; then basefile=$(basename "$1" | sed -e 's/[a-zA-Z0-9._-]/-/g');
url --progress-bar --upload-file "$1" "https://transfer.
sh/$basefile" >> $tmpfile; else curl --progress-bar --upload-file
"$1" "https://transfer.sh/$1" >> $tmpfile;
fi;
cat $tmpfile;
rm -f $tmpfile;
}
```

Log out of your shell and log in again. Now you can use the following *transfer* command:

```
transfer filename.txt
```



You can upload up to 10GB and files will be stored for 14 days. Do remember to encrypt the sensitive files while uploading.

—Ravichandran Somasundaram, rav.adonis@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.