

```

stack: examples/wordpress
version: 0.3.0
variables:
  wordpress-mysql-root:
    type: string
    from:
      vault: wordpress-mysql-root
      random_string: 32
    to:
      vault: wordpress-mysql-root
  wordpress-mysql-password:
    type: string
    from:
      vault: wordpress-mysql-password
      random_string: 32
    to:
      vault: wordpress-mysql-password
services:
  wordpress:
    image: wordpress:4.6
    stateful: true
    ports:
      - 80:80
    environment:
      WORDPRESS_DB_HOST: mysql
      WORDPRESS_DB_USER: wordpress
      WORDPRESS_DB_NAME: wordpress

```

Figure 3: Kontena yml/Part 1

```

$ kontena service show wordpress/wordpress
test/wordpress/wordpress:
  stack: test/wordpress
  status: running
  image: wordpress:4.6
  revision: 2
  stateful: yes
  scaling: 1
  strategy: ha
  deploy_policy:
    elc_health: 0.6
  dns: wordpress-1.wordpress.test.kontena.local
  secrets:
    - secret: wordpress-mysql-password
      name: WORDPRESS_DB_PASSWORD
      type: env
  env:
    - WORDPRESS_DB_HOST=mysql
    - WORDPRESS_DB_USER=wordpress
    - WORDPRESS_DB_NAME=wordpress
  net: bridge
  ports:
    - 80:80/tcp
  instances:
    wordpress-wordpress-1:
      rev: 2016-11-28 13:51:02 UTC
      service_rev: 2
      role: N/A
      ip: 10.81.128.115
      dns: wordpress-1.wordpress.test.kontena.local
      public_ip: 192.0.2.1
      status: running
      exit code: 0

```

Figure 5: Kontena stack output

We will take the WordPress application as an example and deploy it in the Kontena grid.

We need to create a *Kontena.yml* file, which contains all the attributes regarding the application.

You can get the sample *yml* file from the official site at the link <https://kontena.io/docs/getting-started/quick-start>.

Check Figures 3 and 4 for the *yml* file.

Once the *yml* file is created, we can install and deploy our

```

WORDPRESS_DB_HOST: mysql
WORDPRESS_DB_USER: wordpress
WORDPRESS_DB_NAME: wordpress
secrets:
  - secret: wordpress-mysql-password
    name: WORDPRESS_DB_PASSWORD
    type: env
mysql:
  image: mariadb:5.5
  stateful: true
  environment:
    MYSQL_DATABASE: wordpress
    MYSQL_USER: wordpress
  secrets:
    - secret: wordpress-mysql-root
      name: MYSQL_ROOT_PASSWORD
      type: env
    - secret: wordpress-mysql-password
      name: MYSQL_PASSWORD
      type: env

```

Figure 4: Kontena yml Part 2

WordPress stack, as follows:

```
kontena stack install kontena.yml
```

It will take some time to finish this. Once it is over, we can check WordPress and the MySQL service to know whether it's running or not.

```
kontena stack ls
```

By using the *kontena stack* command, we can see the entire configuration of each service.

Figure 5 demonstrates the Kontena 'service show' output for WordPress stack.

To test the WordPress service, we need to use the public IP address mentioned in the Kontena 'service show' command along with TCP port 80. [END](#) 

References

- [1] <https://rubyinstaller.org/downloads/>
- [2] <https://www.kontena.io/docs/core-concepts/architecture.html>
- [3] <https://www.kontena.io/docs/getting-started/quick-start.html>

By: Maulik Parekh

The author has an M. Tech degree in cloud computing from VIT University, Chennai. He can be reached at maulikparekh2@gmail.com. Website: <https://www.linkedin.com/in/maulikparekh2>.