Figure 7: Copying contents from the template to our *myfirstapp* application

means that the app is up and running.

Now, instead of the default page, we use our own home page.

To do that, we have to create a controller that is used as a mediator to go to a specific Web page. Basically, it will control the calls and tell us when we have to call or display which Web page.

Here is the command to create the controller and Web page:

```
rails generate controller welcome homepage
```

'Generate' is the keyword used to create the controller, 'welcome' is a controller name and 'homepage' is the view created under this controller.

Now open your project folder. You will find *myfirstapp* in the text editor (I am using Sublime).

Given below is some information about the contents of the folder and the files associated with it.

App: App is the folder in which we will spend most of our time. It contains the MVC architecture, and there are folders like views, models, mailers, helpers, controllers and assets. Apart from what we already know about MVC, there are helpers, which are small functions or modules used in applications; while assets contain images, CSS and JavaScript files.

Bin: This folder contains all the commands and the set-up utility. Usually, we will not touch this folder.

Config: This folder contains all the configuration files including *database.yml*, which is for database related configuration and *routes.rb*, where we will write routes to call Web pages.

All other folders are of not much use currently, so we will not go deeper into them.

Now, to check our home page, we need to do some modifications. After running the previous controller command, we can look into the folders that are inside the controller and also the views. There are some new files created.

If you can't see the new files created, go to your folder and press F5 or refresh it. Then check for newly created files.

As you can see in Figure 4, we need to create routes so that the request will be directed to our home page. Check line no. 8 inside the *Config/routes.rb* file, uncomment it and replace the word 'index' with the word 'homepage'.

Now reload the browser page and you can see our new sample home page of the Web application.




Figure 8: Web application using agency snapshot-1




Figure 9: Web application using agency snapshot-2



Figure 10: Web application using agency snapshot-3

We can go to *homepage.html.erb* and write code to create the application.

So this is our sample Web application. Now, we will use one of the bootstrap templates and see how effectively and easily we can build a powerful website and customise it.

Go to <https://startbootstrap.com/template-overviews/agency/> and download any template—I have chosen the agency template. Download the agency template Zip file and extract it. Compare it with our *myfirstapp* application and add all CSS, JavaScripts and images from the agency template into *myfirstapp/assets/* and the respective folders. Also, copy *index.html* from the template and paste the contents into *homepage.html.erb*.

If your application, running on localhost: 3000, is taking too much time to reload, go to <http://stackoverflow.com/questions/26318837/slow-localhost-load-running-rails-and->

Continued on Page 71...