

The Tale of Two Cities +

The above code will add line breaks after the '+', so that each book name is displayed in a single line. Now, let us look at some of the basic text formatting options that are often used in your documents.

Text can be made bold by adding an '*' (asterix) character at both ends of the word, as follows:

```
*The Scarlet Pimpernel*
```

Or you can italicise a word by using the '_' (underscore) character wrapped around the word, as shown below:

```
_The Scarlet Pimpernel_
```

These rules can be applied to a single character also. If you want to apply a monospace font style to a particular piece of text, you can use the '``' character, as follows:

```
``The Scarlet Pimpernel``
```

Or you can use multiple styles for a single word or line, as shown below:

```
The **Adventure** _of_ ``_D``ancing`` **M**en
```

To highlight text, enclose the text using '#', as shown below:

```
The Secret #Adversary#
```

There are cases when you want specific words to be in a smaller font. To achieve this effect, add the [small] attribute followed by the '#' enclosing the word as shown below:

```
Mary had a [small]#little# lamb
```

In the same way, you can add a word in a bigger font, as follows:

```
That Polar bear is [big]#huge##
```

The outputs for the above code snippets are displayed in Figure 1.

Tables

Tables in AsciiDoctor have a simple syntax, but offer sophisticated features.

Let's start with the simple example of how to define tables in AsciiDoctor:

```
===
|Alexander Dumas|Charles Dickens
```

```
The Scarlet Pimpernel
The Scarlet Pimpernel
The Scarlet Pimpernel
The Adventure of Kancing Men
The Secret Adversary
Mary had a little lamb
That Polar bear is huge
```

Figure 1: Text formatting

Alexander Dumas	Charles Dickens
Agatha Christie	George Orwell
Sir Arthur Conan Doyle	Wilkie Collins

Figure 2: Sample table

```
|Agatha Christie|George Orwell
|Sir Arthur Conan Doyle|Wilkie Collins
|==
```

The vertical bar with three equal signs (|===) is used to define the boundaries of a table. The default table data format in AsciiDoctor is PSV (pipe separated values). Data is displayed in cells, and each cell is created in AsciiDoctor as soon as a vertical bar (|) is encountered in the code.

Each row shares the same number of cells. If any vertical bar is detected without any data next to it, it will create an empty cell in your table.

cols attribute: When you are creating the cells of a row individually on a consecutive line, you will need to use the cols attribute to specify the number of columns for the table, as shown below:

```
[cols="3"]
|===
|Debian
|Fedora
|RedHat
|Open Suse
|Linux Mint
|Apricity
|===
```

Please note that if you prefer to avoid the cols attribute in your table, your table will be rendered in the number of columns with respect to the number of cells right after the character (|===).

Column alignment: You can align the column content as left, right or centre. In the following code, you can use a different alignment for each column in the table, or you can align all the columns in the same way.

```
[cols="3"]
[cols="<,^,>"]
|===
```