

	This is a local site without Online connections on the Internet.
	A Cautionary Message
	This is a Warning Message
	This is the site for you!!!
	This Site is still a Work in Progress

Figure 8: Admonitions

the bottom of the page. Each footnote is designated for particular elements in the text in AsciiDoctor. Footnotes can be placed by using the `footnote: []` macro.

This is an example of Footnote footnote: [this is the actual footnote, not the other]

Converting to PDF: So far, we have seen our output in HTML format, but what if you need your content in PDF format. To do that, install the *AsciiDoctor-pdf* gem:

```
$ sudo gem install asciidoctor-pdf -pre
```

Once the gem is installed, choose the document that you

© - Copyright ® - Registered™ -Trademark

Figure 9: Textual replacements

This is an example of Footnote ^[1]
1. this is the actual footnote, not the other
Last update 2016-12-27 11:01:31 IST

Figure 10: Footnote

wish to convert to PDF and type the following command in your terminal:

```
$ asciidoctor-pdf article.asc
```

You will find a PDF file in your present working directory with the same name as your AsciiDoctor file. 

By: Magimai Prakash

The author has a B.E. degree in computer science. As he is deeply interested in Linux, he spends most of his leisure time exploring open source.

Continued from Page...58

During collection, all cores clean the garbage in parallel, resulting in shorter pauses; and between garbage collection cycles, neither of the collectors consumes any resources.

Concurrent mark and sweep CMS: This uses the parallel stop-the-world mark-copy algorithm in the Young Generation and, usually, the concurrent mark-sweep algorithm in the Old Generation. This collector avoids long pauses while collecting in the Old Generation, as it does not compact the Old Generation, but uses free lists to manage reclaimed space; and it does most of the job in the mark-and-sweep phases concurrently with the application. This algorithm is divided into seven phases. These are: i) Initial mark, ii) Concurrent mark, iii) Concurrent Pre-clean, iv) Concurrent abortable Pre-clean, v) Final Remark, vi) Concurrent Sweep, and vii) Concurrent Reset.

G1: This is also known as Garbage-First and, with it, you can set specific performance goals. You can request the stop-the-world pauses to be no longer than x milliseconds within any given y-millisecond long time-range, e.g., no more than 5 milliseconds in any given second. Garbage-First GC will do its best to meet this goal with high probability (but not with certainty, as that would be hard to do in real-time). G1 has totally redesigned the way the objects are stored in Heap.



Figure 7: Memory structure of the Heap in G

It does not have the concept of Young and Old generations; instead, the Heap is split into a number of smaller (typically about 2048) Heap regions that can house objects. Each region may be an Eden region, a Survivor region or an Old region, as shown in Figure 7.

With all this information, you are up to date with the different types of garbage collection mechanisms. You can play around with the different GC algorithms by applying them in different generations of the Heap. 

By: Ashish Kumar Sinha

The author is a software engineer based in Bengaluru. A software enthusiast by heart, he is passionate about using open source technology and sharing it with the world. He can be reached at ashi.sinha.87@gmail.com.