



Figure 1: Admin homepage of Solr



Figure 2: Schema.xml



Figure 3: Document import

localhost:8983/Solr/

Now, to start the search in Solr, you first have to create the *core* file, by giving the command *Solr create -c core_name*, in cmd. The *core* file mainly contains configuration files in the *conf* folder.

Solr makes it easy to search for an application. You just have to define a schema according to your dataset in *schema.xml*, which is a file that defines the representation of the documents that are indexed/ingested in Solr, i.e., the set of data fields that they contain. For example, a newspaper article may contain a title, author name, body text, date, etc. You have to mention the data type of those fields in *schema.xml*. Figure 2 shows how to define data fields in *schema.xml*.

After defining Schema, deploy Solr into your data either in the database or by uploading data files. Figure 3 shows how to upload data in Solr in various formats in order to supply Solr documents for each user who searches.

As Solr is based upon open standards, it is highly extensible. Solr fires queries that are RESTful in nature, which means that the query is as simple as an HTTP request URL and the response is an ordered document – mainly, XML, CSV, JSON or some other formats.

Basic syntax, *schema.xml*, with an example

Fields: You can simply define a field name or dataset in *schema.xml* as follows:

```
field name="string" indexed="true"
stored="true" multiValued="true"
required="true"
```

Here, 'name' is the name of the field type. This value is used in field definitions, in the 'type' attribute. 'Indexed' default value is true—the value of the field can be used to query and to retrieve matching documents. The 'stored' default value is true—the actual value of the field can be retrieved by queries. 'multiValued' default value