

Creating a user with the UID: You can create a user with a custom UID with the `-u` option, as follows:

```
[root@localhost bhargab]# useradd -u 1036 anirban
```

Creating a user with non-default home directory:

A non-default home directory can be set by executing the following command:

```
[root@localhost bhargab]# useradd -d /home/test anirban
```

Adding a user to a primary group and supplementary group:

A systems administrator can specify a primary group and a supplementary one by specifying the `-g` and `-G` option, respectively.

```
[root@localhost bhargab]# useradd -g "head" -G "faculty" anirban
```

Locking and unlocking a user: A super user can lock and unlock a user account. To lock an account, one needs to invoke `passwd` with the `-l` option.

```
[root@localhost bhargab]# passwd -l anirban
Locking password for user anirban.
passwd: Success
```

The `-u` option with `passwd` unlock an account, as shown below:

```
[root@localhost bhargab]# passwd -u anirban
Unlocking password for user anirban.
passwd: Success
```

Changing a user name: The `-l` option with the `usermod` command changes the login (user) name, as shown below:

```
[root@localhost bhargab]# usermod -l "nishant" anirban
```

Removing a user: Combining `userdel` with the `-r` option drop a user and the home directory associated with that user, as shown below:

```
[root@localhost bhargab]# userdel -r nishant
```

Linux group

Linux group is a mechanism to organise a collection of users. Like the user ID, each group is also associated with a unique ID called the GID (group ID). There are two types of groups – a primary group and a supplementary group. Each user is a member of a primary group and of zero or 'more than zero' supplementary groups. The group information is stored in `/etc/group` and the respective passwords are stored in the `/etc/gshadow` file. Some

operations such as creating, deleting and modifying on a group are discussed below.

Creating a group with default settings: To add a new group with default settings, run the `groupadd` command as a root user, as shown below:

```
[root@localhost bhargab]# groupadd employee
```

If you wish to add a password, then type `gpasswd` with the group name, as follow:

```
[root@localhost bhargab]# gpasswd employee
Changing the password for group employee
New Password:
Re-enter new password:
```

Creating a group with a specified GID: To explicitly specify the GID of a group, execute the `groupadd` command with the `-g` option, as follow:

```
[root@localhost bhargab]# groupadd -g 1200 manager
```

Removing group password: To remove a group password, run `gpasswd -r` with the relevant group name, as follow:

```
[root@localhost bhargab]# gpasswd -r employee
```

Changing the group's name: To change the *group's* name, run the `groupmod` command with the `-n` option as a super user, as shown below:

```
[root@localhost bhargab]# groupmod -n hrmanager employee
```

Changing the group's GID: To change the GID of a group, run the `groupmod` command with `-g`, as follow:

```
[root@localhost bhargab]# groupmod -g 1050 manager
```

Deleting a group: Before deleting a primary group, delete the users of that primary group. To delete a group, run the `groupdel` command with the group name, as shown below:

```
[root@localhost bhargab]# groupdel employee
```

If you wish to know much more about the user and group management, you can refer to the Red Hat system administration and manual page of each command. 

By: Bhargab Choudhury

The author is interested in information security and systems administration. He can be reached at bhargabchoudhury24@gmail.com.