

```

<meta http-equiv="Content-Type" content="text/html;
charset=utf-8">
<meta property="og:url" content="{{ site.url }}"{{ page.
url | remove_first:'index.html' }}">
<meta property="og:site_name" content="blog.your-domain.
com">

{% if page.title %}
<meta property="og:title" content="{{ page.title }}">
{% endif %}

{% if page.description %}
<meta name="description" content="{{ page.description
}}">
<meta name="og:description" content="{{ page.description
}}">
{% else if page.excerpt %}
<meta name="description" content="{{ page.excerpt |
strip_html | truncatewords: 25 }}">
<meta name="og:description" content="{{ page.excerpt |
strip_html | truncatewords: 25 }}">
{% endif %}

{% if page.og_image_url %}
<meta property="og:image" content="{{ page.og_image_url
}}">
{% else if page.photo_url %}
<meta property="og:image" content="{{ page.photo_url }}">
{% endif %}

{% if page.keywords %}
<meta name="keywords" content="{{ page.keywords }}" />
{% endif %}

{% if page.date %}
<meta property="og:type" content="article">
<meta property="article:published_time" content="{{ page.
date | date: '%Y-%m-%d' }}">
{% endif %}

<script src="//code.jquery.com/jquery-2.1.1.min.js"></
script>

</head>
<body>

<nav class="navbar navbar-default navbar-static-top">
<div class="container">
<!-- Brand and toggle get grouped for better mobile
display-->
<div class="navbar-header">
<button type="button" class="navbar-toggle
collapsed" data-toggle="collapse" data-target="#bs-example-
navbar-collapse-1" aria-expanded="false">

```

```

<span class="sr-only">Toggle navigation</
span>
<span class="icon-bar"></span>
<span class="icon-bar"></span>
<span class="icon-bar"></span>
</button>
<a class="navbar-brand" href="/">Your Blog</a>
</div>
</div> <!-- /.container -->

</nav>

<div class="container">

  {{ content }}

</div>

</body>
</html>

Most of the other views will be generated from this,
which is not at all complicated. You can change it according
to your need.

Next up is app/_layouts/post.html:

---
layout: default
---

<article>
  <header>
    <h1>{{ page.title }}</h1>
    <div class="post-info">
      <div class="author-published">
        by {{ page.author }}
      </div>
      <div class="date-published">
        <time datetime="{{ page.date }}">{{ page.date
| date: '%B %d, %Y' }} </time>
      </div>
    </div>
  </header>

  <div>{{ content }} </div>

</article>

```

Simple stuff, isn't it? Please notice, we are using Jekyll front matter to add some variables that apply only to this template. The front matter is where Jekyll starts to get really cool. Any file that contains a YAML front matter block will be processed by Jekyll as a special file. The front matter must be the first thing in the file, and must take the form of valid YAML set between triple-dashed lines.