

Figure 8: Selecting line ending conversions




Figure 9: Extra options

`cmd`) and go to your project (using `cd`). Git Shell is installed by default with the GitHub Windows installation. To install Bootstrap, enter the following command:

```
C:\>bower install bootstrap -S
```

** In the above code snippet, '-S' means it will save Bootstrap as a dependency for your project in the `bower.json` file.

Now, Bower will automatically install Bootstrap to your project. It recognises that Bootstrap depends on JQuery. So, Bower will automatically install JQuery for us.

In your project folder, Bower has created a `bower_components` folder. The components that Bower fetched and installed are saved in this folder. Now, open the `bower.json` file to see that Bower has added new information about the dependencies.

Updating Bower components

To update Bower components, use the following command:

```
C:\>bower update
```




Figure 10: Successful installation of the package using Bower



Figure 11: bower.json file




Figure 12: Update packages using Bower

Using Bower components

To make use of the Bower components, include CSS and JS scripts into the Web pages. Since all JS and CSS files reside in the `bower_components` folder, we will have to write the following code.

For CSS, the code is:

```
<link href="bower_components/bootstrap/dist/css/bootstrap.min.css" rel="stylesheet">
```

For JS, the code is:

```
<script src="bower_components/jquery/dist/jquery.min.js"></script>
<script src="bower_components/bootstrap/dist/js/bootstrap.min.js"></script>
```

References

- [1] <https://bower.io/>
- [2] <https://git-for-windows.github.io>

By: Shweta Tyagi

The author currently works as a Web developer and tester. Her areas of interest are website development and automation testing.