



TIPS & TRICKS



Install the progress bar in Debian/Ubuntu/Red Hat

`pv` is used to measure the progress of the `dd` command and monitor the progress of data through a pipe. To use this, make sure `pv` is installed in the Linux box. Use the steps given below to install it from repositories.

For Debian/Ubuntu, type:

```
#apt-get install pv
```

For Red Hat/CentOS, type:

```
#yum install pv
```

```
#(pv -n /dev/sda | dd of=/dev/sdb bs=128M conv=notrunc,noerror) 2>&1 | dialog --gauges "Running dd command (cloning), please wait..." 10 70 0
```

Here `-n` is for numeric output, and `dialog --gauges` is used for the dialog box and the message in quotes.



Important note: `dd` (disk clone) should be used very carefully. It can damage the disk, if it is wrongly used.

— Prasanna PNA,
pnprasanna@gmail.com



Transferring files between remote hosts using the command prompt

If you want to copy a file from a remote machine in the same network to your PC, it can be done simply by using the command '`scp`'. The syntax of the command is as follows:

```
# scp username_of_remote_pc@ip_of_remote_pc:file_location location_to_store_in_my_pc
```

For example, if you want to copy a file named 'test.php' located in the directory `/var/www/html/HisWeb` of the PC with ip `172.16.117.49` and user name `R_user` to `/var/www/html/MyWeb` of my PC, the command is:

```
# scp R_user@172.16.117.49:/var/www/html/HisWeb/test.php /var/www/html/MyWeb
```

Then you need to enter the password of `R_user`.

If you want to send a file from your PC to a remote PC, the syntax is:

```
# scp file_to_send username_of_remote_pc@ip_of_remote_pc:file_location location_to_store_in_remote_pc
```

You can also transfer files between two remote PCs. The syntax in this case is:

```
# scp username_of_remote_host_1@ip_remote_host_1:file_to_send username_of_remote_host_2@ip_remote_host_2:location_to_store
```

Enjoy transferring files!

—Md Shakeel Iqbal Saikia,
shakeel.smtp@gmail.com



Get to know more about the process running in Linux

Here is what you can do to know more about the process running in Linux.

1. Create a small process with the `sleep` command:

```
[root@blvrvm15-vm2 proc]# sleep 1000 &
[1] 23735
```

2. The kernel will create a directory related to each process in `/proc`. Go to the folder `/proc/23735`; you can see all the information about the process here. There may be many dynamic results too. To view the details you can use the `cat` command as shown below. `proc` is generally called 'Process Information pseudo-file system'.

```
[root@blvrvm15-vm2 proc]# cd 23735
[root@blvrvm15-vm2 23735]# ll
total 0
dr-xr-xr-x. 2 root root 0 Jan 18 19:17 attr
```