

```
-rw-r--r--. 1 root root 0 Jan 18 19:17 autogroup
-r----- . 1 root root 0 Jan 18 19:17 auxv
-r--r--r--. 1 root root 0 Jan 18 19:17 cgroup
<Output Snipped>
-r--r--r--. 1 root root 0 Jan 18 19:17 status
-r--r--r--. 1 root root 0 Jan 18 19:17 syscall
dr-xr-xr-x. 3 root root 0 Jan 18 19:17 task
-r--r--r--. 1 root root 0 Jan 18 19:17 timers
-rw-r--r--. 1 root root 0 Jan 18 19:17 uid_map
-r--r--r--. 1 root root 0 Jan 18 19:17 wchan
```

```
[root@blvm15-vm2 proc]# cat status
```

The above command will display the complete details of this process.

—**Bhagyaraj M.C.,**
bhagym@india.altair.com

Getting a file using the *telnet* command

Telnet is a very useful command. Here is a tip on how to get files from a website, using *telnet*.

Here is how you can get <http://example.com/test.html> using the *telnet* command:

```
$telnet example.com 80
GET /test.html
```

The output of the above command will display the complete *test.html* file.

—**Remin Raphael,**
remin13@gmail.com

Merge two or more PDF files into a single one

We often need to combine several PDF files into a single PDF file. For this purpose, you can use the *pdfunite* command.

To use the command, you first need to install it on the computer. You can use your OS package manager to do so, as follows:

```
#pdfunite <file1.pdf> <file2.pdf> <output.pdf>
```

The above command merges *file1.pdf* and *file2.pdf* into *output.pdf*.

```
#pdfunite <file1.pdf> <file2.pdf>...<fileN> <output.pdf>
```

The above command merges *file1.pdf*, *file2.pdf* and so on, till *fileN* into *output.pdf*.

pdfunite merges several PDF files in the order of their occurrence on the command line, into one PDF result file. None of the PDFs, *file1* to *fileN*, should be encrypted.

—**Lokeswara Rao Bonta,**
nagarajunice@gmail.com

Track executed commands

It's important for a sysadmin to log all the commands on the production server in order to know how and when the command was executed.

To do this, we can use *Snoopy* for Linux based systems. Installation is simple with the script available from GitHub (the stable version):

```
# wget https://github.com/a2o/snoopy/raw/install/doc/install/bin/snoopy-install.sh
```

```
# chmod u+x snoopy-install.sh
# ./snoopy-install.sh stable
```

Restart the relevant (log) service, if required. Watch the logs as per your *syslog/rsyslog* configuration. In CentOS, it is */var/log/secure*, and for Debian and Ubuntu, it is */var/log/auth.log*.

To make any changes, you can go to the *config* file in */etc/snoopy.ini*.

To disable, run the following command:

```
#snoopy-disable
```

To enable, use the command given below:

```
#snoopy-enable
```

—**Natraj Solai,**
linuxraja@gmail.com

Want to watch a movie in the powerful terminal?

Now, you can watch 'Star Wars' in the terminal. This is one of the exciting things I discovered through this terminal tweak. You need to install the *telnet* package, as follows:

```
$sudo apt-get install telnet
```

Now run the following command:

```
$telnet towei.blinkenlights.nl
```

And the movie begins!

—**Joyce George,**
joycegeo@mail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.