

# The DevOps Series

## Deploying Graphite Using Ansible

In this fifth article in the DevOps series we will learn to install and set up Graphite using Ansible.



**G**raphite is a monitoring tool that was written by Chris Davis in 2006. It has been released under the Apache 2.0 licence and comprises three components:

1. Graphite-Web
2. Carbon
3. Whisper

Graphite-Web is a Django application and provides a dashboard for monitoring. Carbon is a server that listens to time-series data, while Whisper is a database library for storing the data.

### Setting it up

A CentOS 6.8 virtual machine (VM) running on KVM is used for the installation. Please make sure that the VM has access to the Internet. The Ansible version used on the host (Parabola GNU/Linux-libre x86\_64) is 2.2.1.0. The *ansible/* folder contains the following files:

```
ansible/inventory/kvm/inventory
ansible/playbooks/configuration/graphite.yml
ansible/playbooks/admin/uninstall-graphite.yml
```

The IP address of the guest CentOS 6.8 VM is added to the *inventory* file as shown below:

```
graphite ansible_host=192.168.122.120 ansible_connection=ssh
ansible_user=root ansible_password=password
```

Also, add an entry for the *graphite* host in the */etc/hosts* file as indicated below:

```
192.168.122.120 graphite
```

### Graphite

The playbook to install the Graphite server is given below:

```
---
- name: Install Graphite software
  hosts: graphite
  gather_facts: true
  tags: [graphite]

  tasks:
    - name: Import EPEL GPG key
      rpm_key:
        key: http://dl.fedoraproject.org/pub/epel/RPM-GPG-KEY-EPEL-6
      state: present

    - name: Add YUM repo
      yum_repository:
        name: epel
        description: EPEL YUM repo
        baseurl: https://dl.fedoraproject.org/pub/epel/$releasever/$basearch/
        gpgcheck: yes
```