

Running the app

In the app folder, the command *meteor* is executed as follows:

```
FirstMeteorApp >meteor
```

Output

```

▫ Started proxy.
▫ Started MongoDB
▫ Started you app.
▫ App running at: http://localhost:3000/
Type Control-C twice to stop
```

The results of the app can be viewed on the Web browser at the URL <http://localhost:3000/>.

Tags and levels in Meteor

There are three tags in Meteor—head, body and template. These are used to integrate HTML and JavaScript.

MyMeteorApp.html

```

<head>
  <title>MyMeteorApp</title>
</head>
<body>
  <h1>Meteor Programming</h1>
  {{> myAppParagraph}}
</body>
<template name = "myAppParagraph">
  <p>{{mytext}}</p>
</template>
```

MyMeteorApp.js

```

if (Meteor.isClient) {
  // Code for Client-Side
  Template.myAppParagraph.helpers({
    mytext: 'Hello to All'
  });
}
```

Using forms and getting dynamic user data

The form elements are created in the HTML page, as follows:

meteorForm.html

```

<head>
  <title>meteorForm</title>
</head>
<body>
  <div>
    {{> myFormTemplate}}
  </div>
</body>
<template name = "myFormTemplate">
  <form>
```



Figure 4: Displaying the output using MeteorJS

```

  Name <input type = "text" name = "UserForm">
  <input type = "submit" value = "Click Here">
</form>
</template>
```

The JavaScript code is integrated with *submit event*, as shown below:

meteorForm.js

```

if (Meteor.isClient) {
  Template.myFormTemplate.events({
    'submit form': function(event){
      event.preventDefault();
      var mytext= event.target. UserForm.value;
      console.log(mytext);
      event.target.UserForm.value = "";
    }
  });
}
```

Sessions handling in Meteor

Sessions are used to store the data when the app is in use.

The validity of this data is traditionally up to the browsing of the app by the user. Once the user leaves the app, this data is removed with the destruction of the session.

In Meteor, sessions handling is easy to integrate using the session object and, finally, returning the stored data:

meteorSession.html

```

<head>
  <title>meteorSession</title>
</head>
<body>
  <div>
    {{> myMeteorTemplate}}
  </div>
</body>
<template name = "myMeteorTemplate">
</template>
```

To store the data, the *Session.set()* method is used. The *Session.get()* method can be called to retrieve the stored data in the session, as follows:

meteorSession.js