

-nd Don't make new directories; put downloaded files in this one
-N Turn on timestamping
-A.mp3 Download only mp3s
-erobots=off Execute robots.off as if it were a part of .wgetrc

—Vinu K.,
kevy.vinu@gmail.com

Display shell command history with date and time under Linux

Here is a small tip to display the history of a command with the date and time of execution of the command. To display this, you need to define the environment variable as follows:

```
# HISTTIMEFORMAT="%d/%m/%y %T "
```

...or as:

```
echo 'export HISTTIMEFORMAT="%d/%m/%y %T "' >> ~/.bash_profile
```

Here, %d is the day, %m is the month, %y is the year, and %T is the time.

—Munish Kumar,
munishtotech@gmail.com

Copy a file to multiple directories in Linux

You can deploy the `echo` command, a pipe and `xargs` command together with the `cp` command, as shown below, to copy a file to multiple directories in Linux:

```
$ echo /home/remin/Videos/ /home/remin/Downloads/ | xargs -n 1  
cp -v /home/remin/test.txt  
'/home/remin/test.txt' -> '/home/remin/Videos/test.txt'  
'/home/remin/test.txt' -> '/home/remin/Downloads/test.txt'
```

—Remin Raphael,
remin13@gmail.com

Git commands for beginners

With multiple people working on a software project, co-ordination sometimes becomes difficult. Git is a version control system (VCS) for tracking changes in computer files and coordinating work on these files. Given below are a few commands that can be commonly used while using this VCS.

1. Clone remote repo:

```
git clone [repository-uri]
```

2. Refresh repo for the latest from remote repo:

```
git pull
```

3. List all branches:

```
git branch -a
```

4. Switch branch:

```
git checkout [branch-name]
```

5. Check the status for the current repository:

```
git status
```

6. Add new files:

```
git add filename
```

7. Browse past commit information:

```
git log
```

Browse past commit information by using the one line option:

```
git log --oneline
```

8. Check-in changes:

```
git commit -n "Message to commit this file or directory"  
[directory-or-filename]
```

9. Compare file with past revision:

```
git diff cf39cd1 filename
```

10. Reset current branch head (HEAD) to the specified state:

```
git reset <paths>
```

—Sandhya Bankar,
bankarsandhya512@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.