

```

gzip_static on;
expires max;
    add_header Cache-Control "public";
access_log /dev/null;
}
location ~* \.(js|css)$ {
    gzip_static on;
    expires 30d;
        add_header Cache-Control "public";
    }
location ~* \.(ico|gif|jpg|png|svg|JPG|jpeg|webp)$ {
    gzip_static on;
    expires 1M;
    add_header Cache-Control "public";
}

try_files $uri/index.html $uri @puma;
location @puma {

    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header Host $http_host;
    proxy_redirect off;

    proxy_pass http://puma;
}

```

```

server {
    listen 80;
    server_name _;
    root /home/ubuntu/apps/vkaction.com/current/public;
    access_log /home/ubuntu/apps/vkaction.com/current/log/nginx.access.log;
    error_log /home/ubuntu/apps/vkaction.com/current/log/nginx.error.log info;

    location ~ ^/assets/ {
        root /home/ubuntu/apps/vkaction.com/current/public;
        gzip_static on;
        expires max;
        add_header Cache-Control "public";
        access_log /dev/null;
    }
    location ~* \.(js|css)$ {
        gzip_static on;
        expires 30d;
        add_header Cache-Control "public";
    }
    location ~* \.(ico|gif|jpg|png|svg|JPG|jpeg|webp)$ {
        gzip_static on;
        expires 1M;
        add_header Cache-Control "public";
    }
}

try_files $uri/index.html $uri @puma;
location @puma {
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header Host $http_host;
    proxy_redirect off;

    proxy_pass http://puma;
}

```

Figure 1: Nginx configuration

```

proxy_pass http://puma;
}

error_page 500 502 503 504 /500.html;
client_max_body_size 10M;
keepalive_timeout 10;
}

```

Figure 2: Nginx configuration (contd)




Figure 3: Select cloudfront




Figure 4: Create a distribution



Figure 5: Enter the domain name

```

error_page 500 502 503 504 /500.html;
client_max_body_size 10M;
keepalive_timeout 10;
}

```

CDN configuration

In this configuration, the CDN pulls assets from your Web server and caches them. All subsequent requests to that asset will be served straight from the CDN.

1. Login to AWS console and select *Cloudfront* as shown in Figure 3.
2. Click *Create Distribution* as shown in Figure 4.
3. Enter the domain name where your assets are currently located as shown in Figure 5.
4. Customise the object caching. Minimum TTL is set to one day.
5. Enter the alternate domain name, if any, and keep the rest as defaults.
6. Make note of the Cloudfront distribution URL.
7. Enter the Cloudfront distribution URL in the Rails `asset_host` to change the host URL of the assets, as follows:

```

# config/environments/production.rb
config.action_controller.asset_host = "XXXX.cloudfront.net"

```

With this, site performance will be increased and the number of requests hitting the application server will also be reduced. 

By: Jayashree N.

The author is a cloud specialist working with Fcoos Technologies. She has expertise in providing technical solutions related to cloud services, particularly on AWS, Azure and OVH, apart from multiple other platforms.