

probes between the two sites by using the point-to-point layered protocol.

3. As a tunnelling step CIFS share is mapped securely over the Internet. This tunnelling demonstrates the use of extending Corporate CIFS (SMB) file services to a remote satellite office securely over the untrusted public Internet.

Virtual computing

Virtual computing allows PC users remote access to programming applications and procedures when they require it. Users gain access via the Internet through a remote or network server.

Secure virtual computing

Secure virtual computing can be effected by tunnelling services or application protocols within an encrypted secure shell (SSH) session envelope.

Secure virtual computing with Microsoft Remote Desktop Protocol (RDP)

Two NST probes can be arranged for a VPN that tunnels the Remote Desktop Protocol between a terminal services server and a Microsoft terminal service client (mstsc) across the public Internet.



Note: The ISO image of NST 24 can be found with the bundled DVD.



By: Prema Maheshwari

The author has a masters in commerce and is a technology enthusiast. Writing is her hobby. She can be contacted at ca.premamaheshwari@gmail.com.

Continued from page 39...

You can now issue the following command to get the same result:

```
$ ansible ubuntu -m ping -u xetex
```

```
ubuntu | SUCCESS => {
  "changed": false,
  "ping": "pong"
}
```

For the Ubuntu system, you can also add the defined user in the `/etc/ansible/hosts` file as follows:

```
ubuntu ansible_ssh_host=ubuntu ansible_ssh_user=xetex
```

The ping command is now simplified to:

```
$ ansible ubuntu -m ping
```

```
ubuntu | SUCCESS => {
  "changed": false,
  "ping": "pong"
}
```

You can now try the earlier Ansible commands on the target Ubuntu VM as illustrated below:

```
$ ansible ubuntu -a uptime
```

```
ubuntu | SUCCESS | rc=0 >>
12:32:14 up 25 min, 3 users, load average: 0.02, 0.07, 0.06
```

```
$ ansible ubuntu -a date
```

```
ubuntu | SUCCESS | rc=0 >>
Sun Feb  5 12:32:45 IST 2017
$ ansible ubuntu -m setup
ubuntu | SUCCESS => {
  "ansible_facts": {
    "ansible_all_ipv4_addresses": [
      "192.168.122.250"
    ],
    "ansible_all_ipv6_addresses": [
      "ff20::5034:ff:fa9f:6123"
    ],
    "ansible_architecture": "x86_64",
    "ansible_bios_date": "04/01/2014",
    "ansible_bios_version":
      "1.10.1-20151022_124906-anatol",
    "ansible_cmdline": {
      "BOOT_IMAGE": "/boot/vmlinuz-3.19.0-15-generic",
      "quiet": true,
      "ro": true,
      "root": "UUID=f43c2c72-5bc7-4a97-9a43-12e634ae232af",
      "splash": true,
      "vt.handoff": "7"
    },
    ..
  }
```



By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.