

these tasks. The Grunt ecosystem is huge and it's growing every day. Presently, there are more than five thousand plugins available in the Grunt ecosystem to choose from. You can use Grunt to automate just about anything with minimum effort.

ReactJS



ReactJS is an open source JavaScript library for building user interfaces. It is developed by Facebook, Instagram and a

community of individual developers and corporations. It's used for handling the view layer for Web

and mobile apps. ReactJS allows us to create reusable UI components. [END](#) 

References

- [1] <http://www.hongkiat.com/blog/latest-webdev-tools/>
- [2] http://db-engines.com/en/blog_post/55
- [3] <https://angular.io/>
- [4] <https://nodejs.org/en/>
- [5] <http://db-engines.com/en/ranking/search+engine>

By: Roopendra Vishwakarma

The author currently works at Cognizant Technology Solutions as a projects associate. He has written many articles on various technologies, open source software, etc. He can be reached at roopendra@techieroop.com

Continued from page 71...

Embedded C

The standard known as Embedded C is slightly different from all the others. C from K&R C to C11 depicts the changes of a programming language over time, based on user requirements. But the Embedded C standard was proposed to customise the C language in such a way that it can cater to the needs of embedded system programmers. While the other standards of C are improvements over previous standards, Embedded C is a standard that is being developed in parallel. A lot of non-standard features were used in C programs written for embedded systems. Finally, in 2008, the C Standards committee came up with a standardisation document that everyone has to adhere to. Embedded C mostly has the syntax and semantics of normal C with additional features like fixed-point arithmetic, named address spaces, and basic I/O hardware addressing. Two groups of fixed-point data types called the *fract* types and the *accum* types were added to the C language to support fixed-point arithmetic. The keywords *_Fract* and *_Accum* are used for this purpose. New header files like *<iohw.h>* have also been proposed by the Embedded C standards committee. The main advantage of the Embedded C standard is that it is simpler and easier to learn than traditional C.

If you want to learn more about any of these

standards, just search the Internet, particularly the website <http://www.open-std.org/>. I will be very happy if this article motivates somebody to migrate from ANSI C to C11, which was released in 2011. Six years have already elapsed, so it is high time to adopt the C11 standard. As an aside, the latest standard of C++, informally known as C++17, will be finalised in 2017. So, we have the chance to be the early adopters of a new standard of a very popular programming language, rather than be one among the late majority, as in the past.

Before winding up, I want to mention the Turbo C compiler from Borland, which is outdated yet used by a lot of people. Which is the standard supported by the Turbo C compiler? Well, just like for the default standard supported by *gcc*, the answer is also 'None'. The default standard is the whole of ANSI C and some Turbo C specific extensions. Remember, these extensions are not available with *gcc* and this is the reason why header files like *<conio.h>* are not available in Linux. Finally, it took me some time to come up with this pun, "Read this article carefully and you will see that you are not all at sea about C!" [END](#) 

By: Deepu Benson

The author currently works as an assistant professor in Amal Jyothi College of Engineering, Kanjirappally. He maintains a technical blog at www.computingforbeginners.blogspot.in and can be reached at deepumb@hotmail.com.