



Figure 5: Displaying rendered content along with data in a template

```
'OSFY November', 'OSFY December'];
}
});
```

In the route's *model()* function, return the data you want to make available for the template. In this case, pass the list of monthly OSFY issues to the template.

Now, we will render the array of strings, returned by *model()* method, into HTML. Open *magazines.hbs* and add the following code:

```
<h2>List of Editions</h2>
<ul>
```

Continued from page 77...

The various transport operators together could form a consortium and start a blockchain network. In this case, the blockchain is a permissioned one, where the consortium controls who can join its blockchain. Only members of the consortium may be allowed to join the blockchain network. Alternatively, the public Ethereum blockchain network can be used and the smart contract can be deployed on it.

The transport operator may run a Web application on his node with an easy-to-use user interface to create the smart contract on the blockchain. The sender gets into a contract with the transport operator. The terms and conditions of the transportation and payment are coded as a smart contract and deployed on the blockchain. The payment may be locked up in an escrow account.

The sensor data from the shipped container is received by the blockchain nodes and posted to the smart contract, which verifies the recorded temperature/pressure parameters as per the codified terms of the contract. Upon successful delivery of the item, the smart contract will trigger the payment from the escrow account. The payment will be completed in near real-time.

In future, micro payments between machines and M2M (machine-to-machine) communication without human intervention will find wide application. Today's centralised client-server world is being augmented with decentralised, peer-to-peer, disintermediated digital solutions. Blockchains with smart contracts and IoT are the evolving technologies

```
{{#each model as |magazine|}}
<li>{{magazine}}</li>
{{/each}}
</ul>
```

We have used the Handlebar syntax to loop through the data and print it. We have also used each helper to loop over every item in the array we provided from the *model()* hook and print it inside an ** element.

Now, open your browser, start the server and go to <http://localhost:4200/magazines>. You should see the rendered content of *magazines.hbs* along with our main application template, as shown in Figure 5. 

References

- [1] <http://emberjs.com/>
- [2] <https://guides.emberjs.com/v2.10.0/>
- [3] <https://en.wikipedia.org/wiki/Ember.js>

By: Aniket Eknath Kudale

The author has more than two years of experience as a software engineer at Tibco Software Inc., Pune. His interests include Web technologies, computer vision and security. You can reach him at kudale@aniket.co.

which will drive such an exciting world.

Acknowledgements

The authors would like to acknowledge and thank Sriram Rajagopalan and Sarav Daman of Wipro Limited for their critical review of the article and contribution during the implementation of the PoC. 

References

- [1] <https://www.ethereum.org/>
- [2] <https://www.hyperledger.org/>
- [3] <https://www.stellar.org/>
- [4] <http://mqtt.org/>
- [5] <http://www.hivemq.com/demos/websocket-client5>
- [6] https://en.wikipedia.org/wiki/Internet_of_things
- [7] <http://solidity.readthedocs.io/en/develop/>
- [8] <https://www.npmjs.com/package/solc>
- [9] <https://slock.it/>

By: Venkatchalam Subramanian and Sumanta Basu

Venkatchalam Subramanian is a principal consultant in talent transformation, Wipro Limited, Bengaluru. He has 20 years of experience in the IT industry.

Sumanta Basu is a senior architect in the communications vertical, Wipro Limited, Bengaluru. He has more than 12 years of experience in the IT industry.