

port: 3306

Cacti

Cacti is available in the EPEL repository for CentOS. The GPG key for the CentOS repositories is enabled before installing the EPEL repository. A 'yum update' is performed and the Cacti package is installed. A Cacti user is then created in the MySQL database.

```
- name: Install Cacti
  hosts: centos
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [cacti]

tasks:
  - name: Import EPEL GPG key
    rpm_key:
      key: http://dl.fedoraproject.org/pub/epel/RPM-GPG-
KEY-EPEL-6
    state: present

  - name: Add YUM repo
    yum_repository:
      name: epel
      description: EPEL YUM repo
      baseurl: https://dl.fedoraproject.org/pub/
epel/$releasever/$basearch/
      gpgcheck: yes

  - name: Update the software package repository
    yum:
      name: '*'
      update_cache: yes

  - name: Install cacti
    package:
      name: "{{ item }}"
      state: latest
    with_items:
      - cacti

  - name: Create cacti database user
    mysql_user:
      name: cacti
      password: "{{ mysql_cacti_password_hash }}"
      encrypted: yes
      priv: "*,*:ALL,GRANT"
      state: present
```

Fixing a bug

The time zone data is missing in this MySQL version (5.1.73-8). In order to resolve this bug, the `mysql_test_data_timezone`.

`sql` file needs to be imported and the 'cacti' user needs to be given the SELECT privilege to do this.

```
- name: For bug https://github.com/Cacti/cacti/issues/242
  hosts: centos
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [bug]

tasks:
  - name: Import mysql_test_data_timezone.sql
    mysql_db:
      state: import
      name: mysql
      target: /usr/share/mysql/mysql_test_data_timezone.sql

  - name: Grant privileges
    mysql_user:
      name: cacti
      append_privs: true
      priv: 'mysql.time_zone_name:SELECT'
      state: present
```

It is a good practice to have a separate playbook for such exceptional cases. In future, when you upgrade to newer versions that have bug fixes, you can simply skip this step.

Configuration

The last step involves configuring Cacti.

```
- name: Configuration
  hosts: centos
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [config]

tasks:
  - name: Create a database for cacti
    mysql_db:
      name: cacti
      state: present

  - name: Import cacti.sql
    mysql_db:
      state: import
      name: cacti
      target: /usr/share/doc/cacti-1.0.4/cacti.sql

  - name: Update database credentials in config file
    lineinfile:
      dest: /etc/cacti/db.php
      regexp: "{{ item.regexp }}"
```