

```

line: "{{ item.line }}"
with_items:
- { regexp: '^\\$database_username', line: "$database_
username = '{{ mysql_username }}';" }
- { regexp: '^\\$database_password', line: "$database_
password = '{{ mysql_password }}';" }

- name: Allow port 80
  shell: iptables -I INPUT 5 -p tcp --dport 80 -m state
--state NEW,ESTABLISHED -j ACCEPT

- name: Update access in cacti.conf for httpd
  replace:
    dest: /etc/httpd/conf.d/cacti.conf
    regexp: "{{ item.regexp }}"
    replace: "{{ item.replace }}"
  with_items:
    - { regexp: 'Require host localhost', replace:
'Require all granted' }
    - { regexp: 'Allow from localhost', replace: 'Allow
from all' }

- lineinfile:
    dest: /etc/cron.d/cacti
    regexp: '^\\$'
    line: '\\1'
    backrefs: yes

```



Figure 1: License agreement




Figure 2: Pre-installation checks

```

- name: Start mysql server
  service:
    name: mysql
    state: restarted

- wait_for:
    port: 3306

- name: Start the httpd server
  service:
    name: httpd
    state: restarted

- wait_for:
    port: 80

```

A database called 'cacti' is created for the application, and the *cacti.sql* file is imported into it. The database credentials are updated for the Cacti application. The firewall rules are then updated to allow incoming HTTP requests for port 80. The periodic *cron poller* is then enabled in */etc/cron.d/cacti*:




Figure 3: Installation type




Figure 4: Binary location and version