

The following method returns the file's name as well as the line numbers in which the given string is matched.

```
def txt_search_m(self):
    files = [f for f in os.listdir(self.path1) if os.path.
isfile(self.path1+"/"+f)]
    file_number = 0
    for file in files:
        file_t = open(self.path1+"/"+file)
        line_number=1
        flag_file = 0
        for line1 in file_t:
            if self.i:
                line1 = line1.lower()
                if re.search(self.string2, line1):
                    flag_file= 1
                    print "The text "+self.string1+" found in
", file, " at line number ",line_number
                    line_number=line_number+1
            if flag_file == 1:
                file_number=file_number+1
                flag_file=0
        file_t.close()
    print "total files are ",file_number
```

The following method also returns the file's name as well as the line numbers in which the given string is matched. This method works in recursive mode.

```
def txt_search_r(self):
    file_number = 0
    for root, dir, files in os.walk(self.path1, topdown =
True):
        files = [f for f in files if os.path.
isfile(root+"/"+f)]
        for file in files:
            file= root+"/"+file
            file_t = open(file)
            line_number=1
            flag_file = 0
            for line1 in file_t:
                if self.i:
                    line1=line1.lower()

                if re.search(self.string2, line1):
                    flag_file= 1
                    print "The text "+self.string1+" found
in ", file, " at line number ",line_number
                    line_number=line_number+1
            if flag_file == 1:
                file_number=file_number+1
                flag_file=0
            file_t.close()
```

```
print "total files are ",file_number
```

This is the main function of the program which handles all the options. The program offers you six options. The *-m* option gives the number of the file and the line. *-mi* is case-insensitive. You can use the *-h* option to get help for all options.

```
def main():
    parser = argparse.ArgumentParser(version='1.0')
    parser.add_argument('-m', nargs = 2, help = 'To get
files as well as line number of files ')
    parser.add_argument('-s', nargs = 2, help = 'To get the
files contain string ')
    parser.add_argument('-r', nargs = 2, help = 'To search
in recursive order ')
    parser.add_argument('-mi', nargs = 2, help = '-m option
with case insensitive ')
    parser.add_argument('-si', nargs = 2, help = '-s option
with case insensitive ')
    parser.add_argument('-ri', nargs = 2, help = '-r option
with case insensitive ')

    args = parser.parse_args()
```

If you select option *-m*, then it will call the *txt_search_m()* method of class *Text_search()*.

```
try:
    if args.m:
        dir = args.m[1]
        obj1 = Text_search(args.m[0],dir)
        obj1.txt_search_m()
```

If you select option *-s*, then it will call the method *txt_search()*.

```
elif args.s:
    if args.s[1]:
        dir = args.s[1]
        obj1 = Text_search(args.s[0],dir)
        obj1.txt_search()
```

If you select the *-r* option, then it will call the method *txt_search_r()*.

```
elif args.r:
    if args.r[1]:
        dir = args.r[1]
        obj1 = Text_search(args.r[0],dir)
        obj1.txt_search_r()
```

If you select the *-mi* option, then it will call the *txt_search_m()* method in case-insensitive mode.