```
    elif args.mi:
        dir = args.mi[1]
        obj1 = Text_search(args.mi[0],dir,i=1)
        obj1.txt_search_m()
```

If you select option *–s*, then it will call the method *txt_search()* in case-insensitive mode.

```
    elif args.si:
        if args.si[1]:
            dir = args.si[1]
            obj1 = Text_search(args.si[0],dir,i=1)
            obj1.txt_search()
```

If you select the *–r* option, then it will call the *txt_search_r()* method in case-insensitive mode.

```
    elif args.ri:
        if args.ri[1]:
            dir = args.ri[1]
            obj1 = Text_search(args.ri[0],dir,i=1)
            obj1.txt_search_r()

        print "\nThanks for using L4wisdom.com"
        print "Email id mohitraj.cs@gmail.com"
        print "URL: http://l4wisdom.com/see_go.php"

    except Exception as e:
        print e
        print "Please use proper format to search a file use following instructions"
        print "see file-name"
        print "Use <see -h >  For help"
```



Figure 1: Python program to make *exe* file

Figure 2: Option *–s*, which is case-sensitive

```
main()
```

Let's make *exe* files using *pyinstaller* modules as shown in Figure 1.

After conversion, it will make a directory called *see\dist*. Get the *see.exe* files from the directory *see\dist* and put them in the Windows folder. In this way, *see.exe* is added to the system path.

see.exe works like a DOS command.

Let us use the program *see*.

Use the option *–s* as in Figure 2. You can see that only file names are returned.

Use the option *–m* as shown in Figure 3. You can see that file names and lines are returned.

Use the option *–r* as shown in Figure 4. In this option, *–m* works in recursive mode.

Figure 3: Option *–m*, which is case-sensitive



Figure 4: Option *–r*, which is case-sensitive

Figure 5: Option *–si*, which is case-insensitive

Figure 6: Option *–mi*, which is case-insensitive

Continued on page 98...