

```
#
# ServerName gives the name and port that the server uses to identify itself.
# This can often be determined automatically, but we recommend you specify
# it explicitly to prevent problems during startup.
#
# If your host doesn't have a registered DNS name, enter its IP address here.
#
ServerName localhost

#
# Deny access to the entirety of your server's filesystem. You must
# explicitly permit access to web content directories in other
# <Directory> blocks below.
#
<Directory />
    AllowOverride none
    Require all denied
</Directory>
```

Figure 4: Change in ServerName




Figure 6: Editing Environmental variables

typing `www.example.com:80` in the browser search box, we just type `localhost`.

Next, launch the command line tool by typing `cmd` in the search bar of Cortana. Before we start CMD, we need administrative privileges too. Hence, instead of hitting *Enter*, we will hit *Shift+Ctrl+Enter* (or right-click and select *Run as administrator*). Sometimes, to install specific software, we need to run this with administrative privileges.

Then, write the following script:

```
C:\apache24\bin\httpd -k install
```

We now have to configure a number of environmental variables. To do that, right-click on the Windows button and click on *System*. Then, click on *Advanced system settings*. Inside the *Advanced* tab, down below there is a button called *Environmental variables*. Click on it and under *System variables* select *Path*. Click on *Edit* to add some variables. Inside the *Edit environment variables* window, click on *New*

```
Administrator: Command Prompt
Microsoft Windows [Version 10.0.10586]
(C) 2015 Microsoft Corporation. All rights reserved.

C:\Windows\system32>cd C:\Apache24\bin

C:\Apache24\bin>httpd -k install
Installing the 'Apache2.4' service
The 'Apache2.4' service is successfully installed.
Testing httpd.conf....
Errors reported here must be corrected before the service can be started.

C:\Apache24\bin>
```

Figure 5: Installation of Apache Services

```
; The directory under which PHP opens the script using /-username used only
; if nonempty.
; http://php.net/user-dir
user_dir =

; Directory in which the loadable extensions (modules) reside.
; http://php.net/extension-dir
; extension_dir = "."
; On windows:
extension_dir = "ext"
```

Figure 7: Uncommenting *Extension_dir*

to create new variables and add the following:

- C:\PHP
- C:\Apache24
- C:\Apache24\bin

Use the *Move up* or *Move down* button to keep them in order, just to be sure. Click *OK* and close the window.

We can now check whether the Apache settings are correct and if all the servers are set up properly by running the following command in CMD, under administrative privileges:

```
C:\Apache24\bin\httpd -S
```

Some PHP settings have to be edited in order to tell Apache which PHP setting we need to have. Let's access the PHP folder in the C:\ drive. Scroll down and search for the *PHP.ini-development* file and rename it *PHP.ini*.

Let's open this file and uncomment a number of sections.

First search for *extension_dir* and uncomment *extension_dir = "ext"* by removing the semicolon.

To uncomment PHP modules, let's search for *PHP_mysql.dll*. There we have to uncomment two extensions of *my_sql*, which are used along with PHP.

Save the changes.

Let's go back into our command line and then to the root folder, as follows:

```
C:\Windows\System32>cd .. && cd ..
```

To go back one folder, for instance, if we are in C:\ drive and want to access the PHP folder, type:

```
C:\>cd PHP
```

Inside the folder, type the following command:

```
C:\PHP>PHP -m
```

Continued on Page 41...