




Figure 3: Git log dialogue box

shown in Figure 3.

- In the Git log dialogue box, there are three non-editable text boxes. In the top box, you will see the list of commits. The top-most commit is the last one. It will display the commit message, to which the title master will be appended. The commit message will be what you typed in the previous commit. Click on it.
- In the third text box, you will see all the files that have been modified or newly added. In our example, these will be *a.c* and *b.c*.

Now, we have created a new repository and added files to it.

If you make some changes to *a.c* and again see the log, click on *Working dir changes* in the commit box. You will see *a.c* in the file list. So now there are two points—one where you added new files and the second point is *Working directory* where you made new changes. If you want to add these changes as a new commit, right click and select 'Git commit -> master'. Type in the commit message, select the modified files and press OK to commit. Now, if you see the log, you will see two commits—our first one in which we added two new files, and the second one in which we added the modifications in *a.c*. Note that there will be no changes in the 'Working dir changes' section.

Now, if you again make some changes in *a.c* or *b.c* and check the log, you will see these changes in the 'Working dir changes' section. In case you feel that you want to reverse these changes and revert back to the second commit you made, follow the steps listed below.

- Right click and go to *TortoiseGit->Show log*.
- Right click on the commit ID that you want to revert back to. In our case, it will be the latest commit, which is our second one.
- Select the 'Reset master to this' option.




Figure 4: Git clone dialogue box

- Select the reset type as *Hard*. Press OK to reset. If you now check the files, there will be no changes present.

You can check what changes you made in the *Working directory* by going to 'TortoiseGit->Diff'. This will show the list of files that got modified. Double clicking on these files will show the difference in the patch format.

Git cloning in Tortoise Git

If there is any Git repository on the Git server and you need it, then you will have to clone that server. This can be done as follows.

- Right click and select *Git clone*. A clone dialogue box will appear as shown in Figure 4.
- In the URL box, type the web URL of the Git server. In Figure 4, I have used the Web URL of the Linux kernel Git repository.
- In the Directory box, type the path where the clone will be located.
- Press OK to start cloning.

After the cloning is successful, the Git repository from the Git server will be copied to your local folder, where you can make changes and commits. Once all the changes are finished, you can go to 'TortoiseGit->Push...' to push changes to the Git server. **END**

References

- <https://git-scm.com/book/en/v2>
- <https://www.atlassian.com/git/tutorials/>
- <http://www.vogella.com/tutorials/Git/article.html>
- <https://tortoisegit.org/docs/tortoisegit/>
- <https://tortoisegit.org/docs/tortoisegit/tgit-dug.html>

By: Santosh Ramroop Yadav

The author is an embedded systems developer at Bitcomm Technologies Pvt Ltd. His areas of interest are Linux development, microcontroller firmware, networking and RTOS. He can be contacted at santosh678yadav@gmail.com.