

using Linux namespaces, seccomp-bpf and Linux capabilities. Once you install Firejail, you will find it is pretty easy to use. Given below is an example that shows you how to use it. It runs Firefox with the default security profiles.

```
#firejail firefox
```

There are many options available along with Firejail. You can get all the details from the manual page of the command.

—Renjith Thankachan,
mail3renjith@gmail.com



Recording the command session

We often type a sequence of commands in Linux and then forget what we have done. Here is a small tip that will help you record all the commands that you type. The recorded commands will be stored in a readable text file named *file1.txt*.

```
$ script file1.txt
```

```
Script started, file is file1.txt
$ ls
$ ps -el
$ lsblk
$ exit
Script done, file is file1.txt

$ cat file1.txt
```

The output will show all the commands that were executed during the *Script* session.

—Pritam Nipane,
pritamnipane@gmail.com



Creating a desktop launcher in Ubuntu Unity

Unity launchers are actually files stored in your computer with a *.desktop* extension. To create a desktop launcher, create the *.desktop* file using a text editor and save it under the *~/local/share/applications/* directory. For example, given below is the *.desktop* file for Python IDLE.

```
[bash]$ cat ~/.local/share/applications/idle.desktop
[Desktop Entry]
Version=1.0
Type=Application
Name=IDLE
Icon=/media/jarvis/partition/icons/python-icon.png
```

```
Exec=/usr/bin/idle3
Comment=The Drive to Develop
Categories=Development
Terminal=false
StartupWMClass=IDLE
```

All the fields of the above configuration are self-explanatory. Now, you can search the IDLE application in Ubuntu Dash and also lock it to the launcher.

—Narendra Kangralkar, narendrakangralkar@gmail.com



Adding colours to the BASH prompt

To add colours to the shell prompt, use the following export command syntax...

```
\e[x;ym $PS1 \e[m
```

...where,

\e[: Starts the colour scheme
x;y: Indicates the colour pair to use (*x*;*y*)
\$PS1: This is your shell prompt variable
\e[m: Stops the colour scheme

To set a red colour prompt, type the following command:

```
$ export PS1="\e[0;31m[\u@\h \w]\$ \e[m "
```

To set a blue colour prompt, type the following command:

```
$ export PS1="\e[0;34m[\u@\h \w]\$ \e[m "
```

Here is a list of colour codes:

Blue: 0;34
Green: 0;32
Cyan: 0;36
Red: 0;31
Purple: 0;35
Brown: 0;33

—Rajeeb Senapati,
Rajeeb.koomar@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.