

Table 1

Name of the function	Function used for	Syntax of the function
Browser related	<i>Browser ()</i>	Used to instantiate any browser and create a window for it
	<i>browser.visit()</i>	This function is used to navigate to any specific URL
	<i>browser.reload()</i>	Used to reload any Web page
	<i>browser.title</i>	Displays the title of the current active Web page
	<i>browser.html</i>	Used to display the HTML content of the current active Web page
	<i>browser.url</i>	Used to access the URL of the current active Web page
For managing different browser windows actions	<i>browser.windows[0]</i>	Used to access the first window
	<i>browser.windows [window_name]</i>	Used to access any specific window using the <i>window_name</i>
	<i>browser.windows.current ()</i>	Takes you to the current window
	<i>window.is_current ()</i>	Boolean – used to check whether the current window is active or not
	<i>window.next ()</i>	Takes you to the next open window
	<i>window.prev()</i>	Takes you to the previous open window
	<i>window.close()</i>	Closes current window
	<i>window.close_others()</i>	Closes all windows except the current one
For finding elements of any Web page	<i>browser.find_by_name()</i>	Used to find an element using its name
	<i>browser.find_by_css()</i>	Used to find an element using its CSS value
	<i>browser.find_by_xpath()</i>	Used to find an element using its XPath
	<i>browser.find_by_tag()</i>	Used to find an element using its tag name
	<i>browser.find_by_text()</i>	Used to find an element using its text value
	<i>browser.find_by_id()</i>	Used to find an element using its ID value
	<i>browser.find_by_value()</i>	Used to find an element using its value

using the code or command we write. It's advisable to choose `virtualenv` for a good development environment.

Once we have all the development libraries installed for the OS we are using, we just need to install all the Splinter development dependencies using the `make` command. Given below is the command for this.

```
$ [sudo] make dependencies
```

We will use `sudo` while making dependencies only if we are not using `virtualenv`. 

References

- [1] <http://www.wikipedia.org/>
- [2] <https://splinter.readthedocs.io>
- [3] <https://github.com/cobrateam/splinter>

By: Vivek Ratan

The author, who is currently an automation test engineer at Infosys, Pune, has completed his B. Tech in electronics and instrumentation engineering. He can be reached at ratnavivek14@gmail.com for any suggestions or queries.