

```

    name: base-app
---
apiVersion: v1
kind: Service
metadata:
  labels:
    app: httpbin
    name: httpbin
    namespace: base-app
spec:
  ports:
    - name: http
      port: 8000
      targetPort: 80
  selector:
    app: httpbin
    type: ClusterIP
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: httpbin
  namespace: base-app
spec:
  replicas: 1
  selector:
    matchLabels:
      app: httpbin
      version: v1
  template:
    metadata:
      labels:
        app: httpbin
        version: v1
    spec:
      containers:
        - image: docker.io/kennethreitz/httpbin
          imagePullPolicy: IfNotPresent
          name: httpbin
          ports:
            - containerPort: 80
---
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: ingress-httpbin
  namespace: base-app
spec:
  ingressClassName: nginx
  rules:
    - http:
        paths:

```

```

- backend:
    service:
      name: httpbin
      port:
        number: 8000
    path: /
    pathType: Prefix

```

Once done, apply the above application:

```

❏ kubectl apply -f application.yaml
namespace/base-app created
service/httpbin created
deployment.apps/httpbin created
ingress.networking.k8s.io/ingress-httpbin created

```

Now let's check the Ingress:

```

❏ kubectl get ingress -n base-app
NAME                CLASS  HOSTS  ADDRESS  PORTS  AGE
ingress-httpbin     nginx  *      localhost 80      3m17s

```

Let's check that the application is indeed working:

```

❏ curl -s http://localhost | head
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <title>httpbin.org</title>
  <link href="https://fonts.googleapis.com/css?family=Open+Sans:400,700|Source+Code+Pro:300,600|Titillium+Web:400,600,700"
    rel="stylesheet">
  <link rel="stylesheet" type="text/css" href="/flasgger_
static/swagger-ui.css">
  <link rel="icon" type="image/png" href="/static/favicon.
ico" sizes="64x64 32x32 16x16" />

```

This summarises how to use Kind to create a Kubernetes cluster, deploy a NGINX controller, and then use that to deploy a Web application on it. **END** 

References

- [1] Sample application repository: https://github.com/psibi/app_k8s
- [2] Kind homepage: <https://kind.sigs.k8s.io/>

 By: Sibi Prabakaran

The author is a senior engineer working at FPComplete.