

By now, you will have a project folder created on your development machine with various folders and files generated. Locate the folder named *public* in the project folder. We can develop the client application in this folder. The application consists of four important kinds of files like in any other web client: 1) The HTML files, 2) The CSS files, 3) The JS script files, 4) Other assets like images, etc.

Here is the *public/index.html* file for the application:

```
<!DOCTYPE html>
<html>

<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Glarimy Journal</title>
  <link rel="stylesheet" href='./styles.css'>
  <script defer src="/__firebase/8.4.1/firebase-app.js"></script>
  <script defer src="/__firebase/8.4.1/firebase-auth.js"></script>
  <script defer src="/__firebase/8.4.1/firebase-database.js"></script>
  <script defer src="/__firebase/8.4.1/firebase-firestore.js"></script>
  <script defer src="/__firebase/8.4.1/firebase-messaging.js"></script>
  <script defer src="/__firebase/8.4.1/firebase-storage.js"></script>
  <script src='./index.js'></script>
</head>

<body>
  <div id='top'>
    <h1>Our Story</h1>
    <div id='current'></div>
    <div id='nav'>
      <button id='new'> New</button>
      <button id='refresh'>Refresh</button>
      <button id='latest'> Latest</button>
      <button id='oldest'> Oldest</button>
    </div>
  </div>
  <div id='auth'>
    <h2>Login Required</h2>
    <div><input type='text' placeholder="email" id='email' /></div>
    <div><input type='password' placeholder="password" id='password' /></div>
  </div>
```

```
    <input type='submit' value='Login' id='login' />
    <input type='reset' value='Cancel' id='resent' />
  </div>
</div>

<div id='form'>
  <h2>Record Your Story</h2>
  <input type='date' id='date' />
  <div>
    <textarea id='description'></textarea>
  </div>
  <button id='submit'>Record</button>
</div>

<div id='journal'></div>
</body>

</html>
```

Observe that the above HTML file is referring to a file named *index.js* in the same folder. The *index.js* file consists of all the logic. It uses the Firebase SDK extensively. Note that this is the file that also consists of the *firebaseConfig*. Here is the code:

```
const firebaseConfig = {
  apiKey: "AIzaSyXXXXXXXXXXXXXwvZgtbrnLiqKFPE",
  authDomain: "glarimy-firebase.firebaseio.com",
  projectId: "glarimy-firebase",
  storageBucket: "glarimy-firebase.appspot.com",
  messagingSenderId: "7822123479139",
  appId: "1:782281879139:web:aad87vdcdeee3914d256",
  measurementId: "G-F86URYCS0X"
};

var db = undefined;
var user = undefined;

async function login(email, password) {
  await firebase.auth().signInWithEmailAndPassword(email, password);
  user = firebase.auth().currentUser;
}

function activate() {
  document.querySelector('#date').valueAsDate = new Date();
  document.querySelector('#login').
addEventListener('click', async function () {
    let email = document.querySelector('#email').value;
    let password = document.querySelector('#password').value;

    await login(email, password);
    await fetch('desc');
```