

```
+   cat("cyl: ", obj@cyl, "\n")
+   cat("disp: ", obj@disp, "\n")
+ }
+ )
```

```
> m
mpg: 21.4
cyl: 6
disp: 258
```

```
> showMethods(show)
Function: show (package methods)
object="ANY"
object="Car"
object="classGeneratorFunction"
object="classRepresentation"
object="envRefClass"
object="externalRefMethod"
object="genericFunction"
object="genericFunctionWithTrace"
object="MethodDefinition"
object="MethodDefinitionWithTrace"
object="MethodSelectionReport"
object="MethodWithNext"
object="MethodWithNextWithTrace"
object="namedList"
object="ObjectsWithPackage"
object="oldClass"
object="refClassRepresentation"
object="refMethodDef"
object="refObjectGenerator"
object="signature"
object="sourceEnvironment"
object="traceable"
```

The `setMethods()` function accepts the following arguments:

Argument	Description
f	A name of a generic function
signature	Names of formal arguments and classes for the same
definition	A function to be called when method is invoked
where	The environment where the method is defined
sealed	A label to indicate if the class can be redefined

A number of helper functions are available in R for its classes, objects and functions. A few examples are illustrated below:

```
> isS4(m)
[1] TRUE

> isS4(show)
[1] TRUE

> isGeneric("disp")
[1] TRUE

> isGroup(show)
[1] FALSE

> signature("Car")
[1] "Car"

> hasMethod(show)
[1] TRUE
```

```
> getMethod(show)
Method Definition (Class "derivedDefaultMethod"):
```

```
function (object)
showDefault(object)
<bytecode: 0x55ab1e472cd8>
<environment: namespace:methods>
```

Signatures:

```
object
target "ANY"
defined "ANY"
```

You are encouraged to read the manual pages for the above R functions to learn more on their arguments, options and usage. 

References

- India Inflation, consumer prices (annual %), <https://tradingeconomics.com/india/consumer-price-index-cpi>
- Advanced R: The S4 object system, <http://adv-r.had.co.nz/S4.html>

 By: Shakthi Kannan

The author is a free software enthusiast.