

```
date="$word1$word2$word3"
fi
fi

echo -n "Add description: "
read description

echo "$(echo $date | sed 's/ /g')$description" >> $schedule_file

exit 0
```

The code will create a *.schedule* file, which can be read using a proper read command.

Here is more code that allows the user to change the date (from the application):

```
#!/bin/sh

userinput()
{
    echo -n "$1 [$2]:"
    read input
    if [ $(input=$2) -gt $3 ]; then
        echo "$0: $1 $input is found to be invalid"; exit 0
    elif [ "$( $(echo $input | wc -c) - 1 )" -lt $4 ]; then
        echo "$0: $1 $input is very short. Please specify $4"; exit 0
    fi
    eval $1=$input
}

eval $(date +%Y %m %d %H %M %S)

userinput year $year 5000 4
userinput month $mon 12 2
userinput day $day 31 2
userinput hour $hr 24 2
userinput minute $min 59 2

format="$year$month$day$hour$minute"

echo "Setting date to $format. Please enter the root password:"
sudo date $format

exit 0
```

Now, coming to the server side, if you wish to analyse your logs (in the Web server) you can go to a suitable shell script (you can use the method while writing solutions for people working on the server side). For example, the following code analyses the hits from a search engine:

```
#!/bin/sh

maxmatches=50
count=0
```

```
temp="/tmp/$(basename $0)$$"

trap "/bin/rm -f $temp" 0

if [ $# -eq 0 -o ! -f "$1" ]; then
    echo "Please follow this format: $(basename $0) logfile domain" >&2
    exit 1
fi

for URL in $(awk '{ if (length($1) > 4) { print $1 } }' "$1" | \
    grep $2)
do
    args="$(echo $URL | cut -d/? -f2 | tr '&' '\n' | \
    grep -E '(\?q=|\"sid=|\"p=|query=|item=|ask=|name=|topk=)' | \
    cut -d= -f2)"
    echo $args | sed -e 's/+ / /g' -e 's/"/ /g' >> $temp
    count=$(( $count + 1 ))
done
echo "$2 searches from ${1}:"

sort $temp | uniq -c | sort -rn | head - $maxmatches | sed 's/^ / /g'

exit 0
```

Now, let's see how to prepare for the installation of PHP on your server (it can be used if your application needs PHP and is not currently installed):

```
#!/bin/sh

set -e

export DOMAIN="www.yourdomain.com"

SOURCEDIR=$(HOME)/sourcefile
INSTALLDIR=$(HOME)/php5.2.9
DISTDIR=$(HOME)/dist

PHP5="php-5.2.9"
LIBICONV="libiconv-1.12"
ZLIB="zlib-1.2.3"
CURL="curl-7.17.1"
LIBIDN="libidn-0.6.8"
LIBMCrypt="libmcrypt-2.5.7"
LIBXML2="libxml2-2.6.27"
LIBXSLT="libxslt-1.1.18"
MHASH="mhash-0.9.9"
CCLIENT="imap-2004g"
CCLIENT_DIR="imap-2004g"
FREETYPE="freetype-2.3.8"

export PATH=$(INSTALLDIR)/bin:$PATH

function voyage_function_unpack ()
{
    if [ -f $DISTDIR/$1* ]; then
```