

```

echo "Extracting $1";
zcat $(DISTDIR)/$1* | tar -xvf - &>/dev/null;
echo "FINISHED". wait
}

function voyage_funtion_grab () {

    echo "basename $1"
    curl -L --retry 30 --max-time 3600 --retry-delay 60 -# -f --max-redirs 5
--remote-name "$1"
}

echo "---- Downloads and unpacks all prerequisite packages ----"
echo "---- **SOURCEDIR and DISTDIR will be deleted---"
read -p "      (Press any key to continue)" temp;
echo;

if [ -d "$SOURCEDIR" ] || [ -d "$DISTDIR" ] ;then
    echo
    echo "---- Cleaning up. Please wait ----"
    rm -rf $SOURCEDIR $DISTDIR &>/dev/null
    echo "Finished"
    wait
fi

mkdir -p $(SOURCEDIR) $(INSTALLDIR) $(DISTDIR) &>/dev/null

echo
echo "---- Downloading required packages. Please Wait ----"
echo

cd $(DISTDIR)
voyage_funtion_grab http://us.php.net/distributions/$(PHP5).tar.gz
voyage_funtion_grab http://mirrors.usc.edu/pub/gnu/libiconv/
$(LIBICONV).tar.gz
voyage_funtion_grab http://unm.dl.sourceforge.net/sourceforge/mcrypt/
$(LIBMCRCRYPT).tar.gz
voyage_funtion_grab http://xmlsoft.org/libxml2/$(LIBXML2).tar.gz
voyage_funtion_grab http://curl.askapache.com/download/$(CURL).tar.gz
voyage_funtion_grab http://easynews.dl.sourceforge.net/sourceforge/
freetype/$(FREETYPE).tar.gz voyage_funtion_grab ftp://alpha.gnu.org/pub/
gnu/libidn/$(LIBIDN).tar.gz
voyage_funtion_grab ftp://ftp.cac.washington.edu/imap/old/$(CCLIENT).
tar.Z
voyage_funtion_grab ftp://xmlsoft.org/libxml2/$(LIBXSLT).tar.gz
voyage_funtion_grab http://unm.dl.sourceforge.net/sourceforge/mhash/
$(MHASH).tar.gz
voyage_funtion_grab http://www.zlib.net/$(ZLIB).tar.gz

wait
echo "Finished grabbing"

echo "---- The script is unpacking downloaded archives. Please wait ----"

```

```

cd $(SOURCEDIR)
voyage_funtion_unpack $(PHP5)
voyage_funtion_unpack $(LIBICONV)
voyage_funtion_unpack $(LIBMCRCRYPT)
voyage_funtion_unpack $(LIBXML2)
voyage_funtion_unpack $(LIBXSLT)
voyage_funtion_unpack $(MHASH)
voyage_funtion_unpack $(ZLIB)
voyage_funtion_unpack $(CURL)
voyage_funtion_unpack $(LIBIDN)
voyage_funtion_unpack $(CCLIENT)
voyage_funtion_unpack $(FREETYPE)
wait

```

```

echo "-----"
echo "-- Successfully downloaded and unpacked prerequisites for
installation --"
echo "-----"

```

```

exit 0;

```

An 'extra' code

The iTunes list is a very beautiful format, which you can share with others. All your albums will be properly placed on the list. If you can get hold of it, then you can share the list.

The following code will give you an outline:

```

#!/bin/sh

itunehome="$HOME/Music/iTunes"
ituneconfig="$itunehome/iTunes_Music_Library.xml"

musiclibrary="/$(grep ">Music Folder<" "$ituneconfig" | cut -d/- -f9 -| \
cut -d\< -f1 | sed 's/%20/ /g')"
```

echo "Music library is located at \$musiclibrary"

```

if [ ! -d "$musiclibrary" ] ; then
    echo "$0: Music library $musiclibrary is not a directory?" >&2
    exit 1
fi

exec find "$musiclibrary" -type d -mindepth 2 -maxdepth 2 \! -name '*'
-print | sed 's|$musiclibrary/||'
```

With this, we have come to the end of our second segment. I believe we have discussed almost all the topics in the realm. If you have any suggestions, please drop me a line. From the next column onwards, we will address kernel related topics. 

By: Aasis Vinayak PG

The author is a hacker and a free software activist who does programming in the open source domain. He is the developer of V-language—a programming language that employs AI and ANN. His research work/publications are available at www.aasisvinayak.com