

Figure 4: The config dialogue box




Figure 5: Saving an alternate configuration file

```
scripts/kconfig/confdata.c:740: warning: ignoring return value of 'fwrite',
declared with attribute warn_unused_result
In file included from scripts/kconfig/zconf.tab.c:2487:
scripts/kconfig/expr.c: in function 'expr_print_file_helper':
scripts/kconfig/expr.c:1090: warning: ignoring return value of 'fwrite',
declared with attribute warn_unused_result
HOSTLD scripts/kconfig/mconf
scripts/kconfig/mconf arch/x86/Kconfig
```

Note: For the time being, let us set aside the details concerning *confdata.c* and *expr.c*. But you can use the above code as a reference in subsequent discussions.

This will launch a configuration dialogue box that will allow you to configure various aspects with regards to your kernel. You will get an option to save your alternate configuration file and later use the same. This is elucidated in Figures 4 and 5.

You can also see that options like kernel debugging will have an * (asterisk) attached to it, which means that those features are built in.

Now let's go back to the general set-up to make a few changes (see Figure 7). If you stumble upon something new while configuring the kernel, you can rely on the *Help* button.




Figure 6: Built-in options




Figure 7: Changing the configuration

```
root@GNU-BDX:/usr/src/linux-headers-2.6.27-7# make-kpkg clean
user make -f /usr/share/kernel-patchtools/patches/minimal.mk clean
===== making target minimal_clean [now prereq:] =====
Cleaning.
test ! -f .config || cp -f .config.config.precious
test ! -e stamp-building || rm -f stamp-building
test ! -f Makefile || \
    make ARCH=x86_64 distclean
CLEAN scripts/basic
CLEAN scripts/kconfig
CLEAN include/config
make[1]: Leaving directory '/usr/src/linux-headers-2.6.27-7'
test ! -f config.precious || mv -f config.precious config
rm -f modules/modversions.b modules/kysms.ver conf.wars scripts/cramfs/cramfs
scripts/cramfs/mkcramps applied patches stamp-build stamp-configure stamp-image
stamp-headers stamp-src stamp-diff stamp-doc stamp-manual stamp-patch stamp-bui
ldpackage stamp-debian
root@GNU-BDX:/usr/src/linux-headers-2.6.27-7#
```

Figure 8: Running *make clean*

After making the changes, we can save the new configuration and exit:

```
# using defaults found in /boot/config-2.6.27-7-generic
#
#
# configuration written to .config!
#
```

*** End of Linux kernel configuration.

*** Execute 'make' to build the kernel or try 'make help'.

Time for a *make clean*? Refer to Figure 8 for a