

...the resulting array will contain elements that have their class set to `msgdiv` or an element that has an ID equal to `msgdiv`. The same set of elements can also be matched using the jQuery function `add()`.

```
$('#msgdiv').add('#msgdiv')
```

Form selectors

Form selectors help us to select an element based on its type. Though the same result could be achieved using an attribute selector (as we will see), the form selector provides a shorter way. As an example, `:button` will select all the `<input type="button">` elements. Table 1 lists all form selectors.

Form selectors		
Selector	Function	Examples
<code>:hidden</code> , <code>:text</code> , <code>:password</code> , <code>:checkbox</code> , <code>:image</code> , <code>:file</code> , <code>:submit</code> , <code>:reset</code> , <code>:radio</code>	To select all the corresponding <code><type></code> elements, <code><input type=<type> ></code>	<code>\$('#hidden')</code> , will select all the hidden elements
<code>:input</code>	To select all the input elements like text area	<code>\$('#input')</code>
<code>:button</code>	Will select all the button elements that include <code><input type="button"></code> , <code><input type="submit"></code> & <code><input type="reset"></code>	

Table 1

Form filters also help us in making a selection based on the state of a particular element, like *enabled*, *selected*, etc. as shown in Table 2.

Form filters		
Filter	Function	Examples
<code>:enabled</code>	All elements in an enabled state	<code>\$('#:enabled')</code>
<code>:disabled</code>	All elements that are in a disabled state	<code>\$('#:disabled')</code>
<code>:checked</code>	Radio buttons and check boxes that are checked	<code>\$('#:checked')</code> to select all the radio buttons/check boxes that are selected by the user
<code>:selected</code>	Option elements that are selected	<code>\$('#select option:selected')</code> will find the currently selected option

Table 2

The power of form selectors can be understood when two or more of them are combined. For example, `$('#radio:`

```

1 <html xmlns="http://www.w3.org/1999/xhtml" <!-- ... -->
2 <head>
3   <title>Hierarchy Selectors</title>
4   <script type="text/javascript" src="jquery-1.3.2.js"></script>
5 </head>
6 <body>
7   <ul id="upperul">
8     <li>Outer li</li>
9     <li>Inner li</li>
10    <li id="innerul">
11      <li>Inner li</li>
12      <li>Inner li</li>
13    </li>
14  </ul>
15  <input type="text" name="innerTextbox" value="Inner Textbox" />
16  <input type="button" name="innerSubmit" value="Submit" /> <input type="button" name="innerReset" value="Reset" />
17  </body>
18 </html>

```

Figure 1: Hierarchy selectors

`checked')` will select the radio buttons that are selected by the user.

Hierarchy selectors

These selectors are used to select elements based on their positions with respect to other elements. There are four ways, using which we will be able to select an element based on its hierarchy in the DOM. Let's look at the HTML snippet example shown in Figure 1 to explain hierarchy selectors. Table 3 lists hierarchy selectors.

Hierarchy selectors		
Selector	Function	Examples (as per the HTML snippet in Figure 1)
<code>\$(parent child)</code>	To select all the child elements that are under the specified parent. The child can be directly under the parent or can also be the grand child of the parent	<code>\$('#upperul li')</code> will select all the four li(s). Two directly under UL and two under innerul.
<code>\$(parent > child)</code>	To select all the child elements that are 'directly' under the specified parent	<code>\$('#upperul > li')</code> will select only the first two li elements. Since the next two li elements are not directly under <code>#upperul</code>
<code>\$(previous ~ next)</code>	To select all the next elements (only siblings) that are after the previous element	<code>\$('#text ~ :button')</code> will select both the buttons
<code>\$(previous + next)</code>	To select all the next (only siblings) elements that are placed 'immediately' after the previous element	<code>\$('#text + :button')</code> will select only the first button element

Table 3

Filters

Filters are used to select a subset of elements from a set of elements. These filters are extremely useful when combined with the selectors that we have seen previously.